

PRODUCT DATASHEET

ES-HG-S01-F11-R50

Precision Transmission Component

Harmonic Component Sets | Cup Component Set

Product Overview

Precision Transmission Component with rated Torque 3.5 Nm, instantaneous Maximum Torque 17 Nm and start/Stop Peak Torque 8.3 Nm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	3.5	Nm
Instantaneous Maximum Torque	17	Nm
Start/Stop Peak Torque	8.3	Nm
Reduction Ratio	50	
Backlash	≤30	arc sec
Maximum Input Speed	8500	r/min
Allowable Average Torque	5.5	Nm
Frame Size	11	
Weight	0.13	kg

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	3.5	Nm	Frame Size: 11; Reduction Ratio: 50
Instantaneous Maximum Torque	17	Nm	Frame Size: 11; Reduction Ratio: 50
Start/Stop Peak Torque	8.3	Nm	Frame Size: 11; Reduction Ratio: 50
Backlash	≤30	arc sec	Frame Size: 11; Reduction Ratio: 50
Allowable Average Torque	5.5	Nm	Frame Size: 11; Reduction Ratio: 50
MECHANICAL			
Frame Size	11		Frame Size: 11; Reduction Ratio: 50
Weight	0.13	kg	Frame Size: 11; Reduction Ratio: 50
Wave Generator Bore U	φ5H7 / φ6H7		Frame Size: 11; Option Label: Wave generator - A φ5; Reduction Ratio: 50; Wave Generator Option: wave-generator-9b68021d3e2c / Frame Size: 11; Option Index: 1; Option Label: Wave generator - A φ6; Reduction Ratio: 50; Wave Generator Option: wave-generator-4df7ad827c47
RELIABILITY			
Design Life	10000	h	Frame Size: 11; Reduction Ratio: 50
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	50		Frame Size: 11; Reduction Ratio: 50
Maximum Input Speed	8500	r/min	Frame Size: 11; Reduction Ratio: 50
Average Input Speed	3500	r/min	Frame Size: 11; Reduction Ratio: 50

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	11	
Weight	0.13	kg
Wave Generator Bore U	φ5H7 / φ6H7	

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.