

PRODUCT DATASHEET

ES-HG-S03-F17-R80

Precision Transmission Component

Harmonic Component Sets | High-Torque Cup Component Set

Product Overview

Precision Transmission Component with rated Torque 29 Nm, instantaneous Maximum Torque 113 Nm and start/Stop Peak Torque 56 Nm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	29	Nm
Instantaneous Maximum Torque	113	Nm
Start/Stop Peak Torque	56	Nm
Reduction Ratio	80	
Backlash	≤20	arc sec
Maximum Input Speed	7300	r/min
Allowable Average Torque	35	Nm
Frame Size	17	
Weight	0.15	kg

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	29	Nm	Frame Size: 17; Reduction Ratio: 80
Instantaneous Maximum Torque	113	Nm	Frame Size: 17; Reduction Ratio: 80
Start/Stop Peak Torque	56	Nm	Frame Size: 17; Reduction Ratio: 80
Backlash	≤20	arc sec	Frame Size: 17; Reduction Ratio: 80
Allowable Average Torque	35	Nm	Frame Size: 17; Reduction Ratio: 80
MECHANICAL			
Frame Size	17		Frame Size: 17; Reduction Ratio: 80
Weight	0.15	kg	Frame Size: 17; Reduction Ratio: 80
Wave Generator Dimension T	9.4+0.10 / 12.8+0.10	mm	Frame Size: 17; Option Label: Wave generator - A φ8; Reduction Ratio: 80; Wave Generator Option: wave-generator-e6e55a341aa3 / Frame Size: 17; Option Index: 1; Option Label: Wave generator - A φ11; Reduction Ratio: 80; Wave Generator Option: wave-generator-fd26f6670d9b
Wave Generator Bore U	φ8H7 / φ11H7		Frame Size: 17; Option Label: Wave generator - A φ8; Reduction Ratio: 80; Wave Generator Option: wave-generator-e6e55a341aa3 / Frame Size: 17; Option Index: 1; Option Label: Wave generator - A φ11; Reduction Ratio: 80; Wave Generator Option: wave-generator-fd26f6670d9b
Wave Generator Keyway W	4JS9/P9 / 3JS9/P9		Frame Size: 17; Option Index: 1; Option Label: Wave generator - A φ11; Reduction Ratio: 80; Wave Generator Option: wave-generator-fd26f6670d9b / Frame Size: 17; Option Label: Wave generator - A φ8; Reduction Ratio: 80; Wave Generator Option: wave-generator-e6e55a341aa3
RELIABILITY			
Design Life	15000	h	Frame Size: 17; Reduction Ratio: 80
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	80		Frame Size: 17; Reduction Ratio: 80
Maximum Input Speed	7300	r/min	Frame Size: 17; Reduction Ratio: 80
Average Input Speed	3500	r/min	Frame Size: 17; Reduction Ratio: 80

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	17	
Weight	0.15	kg
Wave Generator Dimension T	9.4+0.10 / 12.8+0.10	mm
Wave Generator Bore U	φ8H7 / φ11H7	
Wave Generator Keyway W	4JS9/P9 / 3JS9/P9	


Dimensional Drawings




Mechanical View 1



Mechanical View 2



Mechanical View 3



Mechanical View 4

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Overall axial length	26.5 mm
	Axial length with unilateral tolerance	20 mm +0.4/0
	End axial length	6.5 mm
	Minimum axial distance	Minimum 19 mm
	Minimum end clearance	Minimum 1 mm
	Local step width	3.9 mm
	Minimum outside diameter	Minimum diameter 45 mm
	Fit outside diameter	Diameter 47 mm h7
	Diameter dimension	Diameter 27.2 mm
	Hole diameter fit	Diameter 10 mm H7
	Datum D	
	Axial dimension with tolerance	12.5 mm +0/-0.1
	Right-side minimum outside diameter	Minimum diameter 45 mm
	Diameter dimension	Diameter 28 mm
	Fit outside diameter	Diameter 60 mm h6
	Bottom axial dimension	13.1 mm ±0.2
	Component label	WAVE GENERATOR-A

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 2	Flange mounting hole quantity and diameter	6 holes, diameter 5.5 mm
	Central hole diameter	Diameter 19 mm
Mechanical View 3	Twenty holes diameter	20 holes, diameter 3.5 mm
	Slot width W	W dimension designation, numeric value not specified in crop
	Diameter 54	Diameter 54 mm
	U designation	U designation, numeric value not specified in crop
	A datum or section identifier	A identifier
	Two M4 threaded holes	2 × M4 threaded holes
	Diameter 22 hole	Diameter 22 mm
Mechanical View 4	View direction	View D
	Diameter callout	Diameter 16 mm
	Threaded hole specification with through-hole diameter	2 × M2.5, Ø11 hole through
	Depth-style callout	Depth-style symbol 5 mm
	Inner diameter callout	Diameter 12 mm

[View Product Online](#)
[Request Engineering Data](#)
[Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.