

PRODUCT DATASHEET

ES-HG-S04-F14-R80

Precision Transmission Component

Harmonic Component Sets | High-Torque Hat Component Set

Product Overview

Precision Transmission Component with rated Torque 10 N·m, instantaneous Maximum Torque 61 N·m and start/Stop Peak Torque 30 N·m.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	10	N·m
Instantaneous Maximum Torque	61	N·m
Start/Stop Peak Torque	30	N·m
Reduction Ratio	80	
Backlash	≤20	arc sec
Maximum Input Speed	8500	r/min
Allowable Average Torque	14	N·m
Frame Size	14	
Weight	0.14	kg

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	10	Nm	Frame Size: 14; Reduction Ratio: 80
Instantaneous Maximum Torque	61	Nm	Frame Size: 14; Reduction Ratio: 80
Start/Stop Peak Torque	30	Nm	Frame Size: 14; Reduction Ratio: 80
Backlash	≤20	arc sec	Frame Size: 14; Reduction Ratio: 80
Allowable Average Torque	14	Nm	Frame Size: 14; Reduction Ratio: 80
MECHANICAL			
Frame Size	14		Frame Size: 14; Reduction Ratio: 80
Weight	0.14	kg	Frame Size: 14; Reduction Ratio: 80
Wave Generator Dimension T	9.4+0.10 / 12.8+0.10 / 16.3+0.10	mm	Varies by published configuration.
Wave Generator Bore U	φ11H7 / φ8H7 / φ14H7		Varies by published configuration.
Wave Generator Keyway W	4JS9/P9 / 3JS9/P9 / 5JS9/P9		Varies by published configuration.
RELIABILITY			
Design Life	15000	h	Frame Size: 14; Reduction Ratio: 80
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	80		Frame Size: 14; Reduction Ratio: 80
Maximum Input Speed	8500	r/min	Frame Size: 14; Reduction Ratio: 80
Average Input Speed	3500	r/min	Frame Size: 14; Reduction Ratio: 80

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	14	
Weight	0.14	kg
Wave Generator Dimension T	9.4+0.10 / 12.8+0.10 / 16.3+0.10	mm
Wave Generator Bore U	φ11H7 / φ8H7 / φ14H7	
Wave Generator Keyway W	4JS9/P9 / 3JS9/P9 / 5JS9/P9	

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.