

PRODUCT DATASHEET

ES-HG-S06-F14-R50

Precision Transmission Component

Cup Harmonic Gearboxes | High-Torque Cup Unit Type II

Product Overview

Precision Transmission Component with rated Torque 7 Nm, instantaneous Maximum Torque 46 Nm and start/Stop Peak Torque 23 Nm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	7	Nm
Instantaneous Maximum Torque	46	Nm
Start/Stop Peak Torque	23	Nm
Reduction Ratio	50	
Backlash	≤20 / 20	arc sec
Maximum Input Speed	8500	r/min
Allowable Average Torque	9	Nm
Frame Size	14	
Weight	0.51	kg

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	7	Nm	
Instantaneous Maximum Torque	46	Nm	
Start/Stop Peak Torque	23	Nm	
Backlash	≤ 20 / 20	arc sec	
Allowable Average Torque	9	Nm	
Angular Transmission Accuracy	1.5	arc min	
Hysteresis Loss	2	arc min	
Starting Torque	4.5 / 0.045	Nm	
MECHANICAL			
Frame Size	14		
Weight	0.51	kg	
Wave Generator Dimension T	7+0.10 / 9.4+0.10	mm	Varies by published configuration.

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Wave Generator Bore U	$\phi 6H7 / \phi 8H7$		Varies by published configuration.
Wave Generator Keyway W	2JS9/P9 / 3JS9/P9		Varies by published configuration.
RELIABILITY			
Design Life	10000	h	
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	50		
Maximum Input Speed	8500	r/min	
Average Input Speed	3500	r/min	
Torsional Rigidity K1	0.34 / 3400	Nm/rad	
Torsional Rigidity K2	0.47 / 4700	Nm/rad	
Torsional Rigidity K3	0.57 / 5700	Nm/rad	
Torsional Rigidity T2	6.9	Nm	
Torsional Rigidity T1	2	Nm	

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	14	
Weight	0.51	kg
Wave Generator Dimension T	7+0.10 / 9.4+0.10	mm
Wave Generator Bore U	φ6H7 / φ8H7	
Wave Generator Keyway W	2JS9/P9 / 3JS9/P9	

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.