

PRODUCT DATASHEET

ES-HG-S07-F50-R100

Precision Transmission Component

Hat Harmonic Gearboxes | High-Torque Hat Unit Type I

Product Overview

Precision Transmission Component with rated Torque 611 Nm, instantaneous Maximum Torque 2678 Nm and start/Stop Peak Torque 1247 Nm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	611	Nm
Instantaneous Maximum Torque	2678	Nm
Start/Stop Peak Torque	1247	Nm
Reduction Ratio	100	
Maximum Input Speed	3500	r/min
Allowable Average Torque	866	Nm
Backlash	≤20	arc sec
Frame Size	50	
Weight	9.6	kg

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	611	Nm	Frame Size: 50; Reduction Ratio: 100; Size: 50
Instantaneous Maximum Torque	2678	Nm	Frame Size: 50; Reduction Ratio: 100; Size: 50
Start/Stop Peak Torque	1247	Nm	Frame Size: 50; Reduction Ratio: 100; Size: 50
Backlash	≤20	arc sec	Reduction Ratio: 100; Size: 50; Frame Size: 50
Allowable Average Torque	866	Nm	Frame Size: 50; Reduction Ratio: 100; Size: 50
Starting Torque	64 / 0.64	Nm	Frame Size: 50; Reduction Ratio: 100; Size: 50 / Reduction Ratio: 100; Size: 50; Frame Size: 50
Angular Transmission Accuracy	1	arcmin	Frame Size: 50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 50
Hysteresis Loss	1	arcmin	Frame Size: 50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 50
MECHANICAL			
Frame Size	50		Frame Size: 50; Reduction Ratio: 100; Size: 50
Weight	9.6	kg	Frame Size: 50; Reduction Ratio: 100; Size: 50
Wave Generator Dimension T	21.8+0.10 / 25.3+0.10 / 24.8+0.10	mm	Varies by published configuration.
Wave Generator Bore U	φ22H7 / φ19H7		Varies by published configuration.
Wave Generator Keyway W	8JS9/P9 / 6JS9/P9		Varies by published configuration.

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
RELIABILITY			
Design Life	15000	h	Frame Size: 50; Reduction Ratio: 100; Size: 50
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	100		Frame Size: 50; Reduction Ratio: 100; Size: 50
Maximum Input Speed	3500	r/min	Frame Size: 50; Reduction Ratio: 100; Size: 50
Average Input Speed	2500	r/min	Frame Size: 50; Reduction Ratio: 100; Size: 50
Wave Generator T	21.8 ⁺ 0.1 ₀ / 24.8 ⁺ 0.1 ₀ / 25.3 ⁺ 0.1 ₀	mm	Varies by published configuration.
Wave Generator U	φ19H7 / φ22H7		Varies by published configuration.
Wave Generator W	6JS9/P9 / 8JS9/P9		Varies by published configuration.
Torsional Rigidity K2	40	×10 ⁴ Nm/rad	Frame Size: 50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 50
Torsional Rigidity K1	25	×10 ⁴ Nm/rad	Frame Size: 50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 50
Torsional Rigidity K3	44	×10 ⁴ Nm/rad	Frame Size: 50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 50
Torsional Rigidity T2	382	Nm	Frame Size: 50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 50
Torsional Rigidity T1	108	Nm	Frame Size: 50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 50

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Overall width	63 mm
	Partial width	39 mm
	End step width	5 mm
	Maximum clearance	MAX 2.5 mm
	Minimum clearance	MIN 2 mm
	Outer diameter with deviations	Diameter 214 mm, upper deviation -0.02 mm, lower deviation -0.05 mm
	Bore diameter fit	Diameter 175 H7
	Maximum diameter limit	MAX diameter 113 mm
	Minimum diameter limit	MIN diameter 133 mm
	Shaft diameter fit	Diameter 170 h6
	Outer diameter fit	Diameter 214 h7
	Datum T	
	Datum D	
	Component label	Wave Generator A
	Bottom partial width	26.8 mm, upper deviation 0 mm, lower deviation -0.1 mm
		29.2 ±0.2 mm

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 2	Tapped holes, 16x M8, depth 12mm, evenly distributed	16× M8 threaded holes, depth 12 mm, evenly distributed on bolt circle
	Through/counterbore holes, 16x $\varnothing 9$, depth 22mm, evenly distributed	16× $\varnothing 9$ mm holes, depth 22 mm, evenly distributed on bolt circle
	Flange outer diameter $\varnothing 154$ mm	$\varnothing 154$ mm
	Process holes × 4	4× process holes (tooling/assembly aid holes)
	Tapped holes, 4x M5	4× M5 threaded holes
Mechanical View 3	Through hole quantity and diameter	12 holes, diameter 9 mm
	M5 set screw quantity	6 M5 set screws
	Hole angular spacing	15 degree angular spacing
	Bolt circle diameter	Diameter 200 mm bolt circle
Mechanical View 4	View designation	View D
	Diameter 32	Diameter 32 mm
	Diameter 26	Diameter 26 mm
	Two M3 threaded holes	2x M3 threaded holes
	Thread hole depth	Depth 6 mm

[View Product Online](#)
[Request Engineering Data](#)
[Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.