

PRODUCT DATASHEET

ES-HG-S08-F14-R80

Precision Transmission Component

Hat Harmonic Gearboxes | High-Torque Hat Unit Type II

Product Overview

Precision Transmission Component with rated Torque 10 N·m, instantaneous Maximum Torque 61 N·m and start/Stop Peak Torque 30 N·m.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	10	N·m
Instantaneous Maximum Torque	61	N·m
Start/Stop Peak Torque	30	N·m
Reduction Ratio	80	
Maximum Input Speed	8500	r/min
Allowable Average Torque	14	N·m
Backlash	≤20	arc sec
Frame Size	14	
Weight	0.7	kg

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	10	Nm	Frame Size: 14; Reduction Ratio: 80; Size: 14
Instantaneous Maximum Torque	61	Nm	Frame Size: 14; Reduction Ratio: 80; Size: 14
Start/Stop Peak Torque	30	Nm	Frame Size: 14; Reduction Ratio: 80; Size: 14
Backlash	≤20	arc sec	Reduction Ratio: 80; Size: 14; Frame Size: 14
Allowable Average Torque	14	Nm	Frame Size: 14; Reduction Ratio: 80; Size: 14
Starting Torque	3.1 / 0.031	Nm	Frame Size: 14; Reduction Ratio: 80; Size: 14 / Reduction Ratio: 80; Size: 14; Frame Size: 14
Angular Transmission Accuracy	1.5	arcmin	Frame Size: 14; Reduction Ratio: 80; Reduction Ratio Min: 50; Size: 14
Hysteresis Loss	1	arcmin	Frame Size: 14; Reduction Ratio: 80; Reduction Ratio Min: 50; Size: 14
MECHANICAL			
Frame Size	14		Frame Size: 14; Reduction Ratio: 80; Size: 14
Weight	0.7	kg	Frame Size: 14; Reduction Ratio: 80
Wave Generator Dimension T	7+0.10 / 9.4+0.10	mm	Frame Size: 14; Option Index: 1; Option Label: Wave generator - A φ 6; Reduction Ratio: 80; Wave Generator Option: wave-generator-39713db786bd / Frame Size: 14; Option Index: 2; Option Label: Wave generator - A φ8; Reduction Ratio: 80; Wave Generator Option: wave-generator-e6e55a341aa3
Wave Generator Bore U	φ6H7 / φ8H7		Varies by published configuration.
Wave Generator Keyway W	2JS9/P9 / 3JS9/P9		Frame Size: 14; Option Index: 1; Option Label: Wave generator - A φ 6; Reduction Ratio: 80; Wave Generator Option: wave-generator-39713db786bd / Frame Size: 14; Option Index: 2; Option Label: Wave generator - A φ8; Reduction Ratio: 80; Wave Generator Option: wave-generator-e6e55a341aa3

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
RELIABILITY			
Design Life	15000	h	Frame Size: 14; Reduction Ratio: 80; Size: 14
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	80		Frame Size: 14; Reduction Ratio: 80; Size: 14
Maximum Input Speed	8500	r/min	Frame Size: 14; Reduction Ratio: 80; Size: 14
Average Input Speed	3500	r/min	Frame Size: 14; Reduction Ratio: 80; Size: 14
Wave Generator T	$7^{+0.1_0} / 9.4^{+0.1_0}$	mm	Reduction Ratio: 80; Size: 14; Frame Size: 14; Option Index: 1 / Reduction Ratio: 80; Size: 14; Frame Size: 14; Option Index: 2
Wave Generator U	$\phi 6H7 / \phi 8H7$		Varies by published configuration.
Wave Generator W	2JS9/P9 / 3JS9/P9		Reduction Ratio: 80; Size: 14; Frame Size: 14; Option Index: 1 / Reduction Ratio: 80; Size: 14; Frame Size: 14; Option Index: 2
Torsional Rigidity K2	0.61	$\times 10^4$ Nm/rad	Frame Size: 14; Reduction Ratio: 80; Reduction Ratio Min: 50; Size: 14
Torsional Rigidity K1	0.47	$\times 10^4$ Nm/rad	Frame Size: 14; Reduction Ratio: 80; Reduction Ratio Min: 50; Size: 14
Torsional Rigidity K3	0.71	$\times 10^4$ Nm/rad	Frame Size: 14; Reduction Ratio: 80; Reduction Ratio Min: 50; Size: 14
Torsional Rigidity T2	6.9	Nm	Frame Size: 14; Reduction Ratio: 80; Reduction Ratio Min: 50; Size: 14
Torsional Rigidity T1	2	Nm	Frame Size: 14; Reduction Ratio: 80; Reduction Ratio Min: 50; Size: 14

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	14	
Weight	0.7	kg
Wave Generator Dimension T	7+0.10 / 9.4+0.10	mm
Wave Generator Bore U	φ6H7 / φ8H7	
Wave Generator Keyway W	2JS9/P9 / 3JS9/P9	

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.