

PRODUCT DATASHEET

ES-HG-S09-F25-R50

Precision Transmission Component

Hollow Shaft Harmonic Gearboxes | High-Torque Hollow Shaft Gear Unit

Product Overview

Precision Transmission Component with rated Torque 51 Nm, instantaneous Maximum Torque 242 Nm and start/Stop Peak Torque 127 Nm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	51	Nm
Instantaneous Maximum Torque	242	Nm
Start/Stop Peak Torque	127	Nm
Reduction Ratio	50	
Maximum Input Speed	5600	r/min
Allowable Average Torque	72	Nm
Backlash	≤20	arc sec
Frame Size	25	
Weight	2.02	kg

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	51	N·m	Frame Size: 25; Reduction Ratio: 50; Size: 25
Instantaneous Maximum Torque	242	N·m	Frame Size: 25; Reduction Ratio: 50; Size: 25
Start/Stop Peak Torque	127	N·m	Frame Size: 25; Reduction Ratio: 50; Size: 25
Backlash	≤20	arc sec	Reduction Ratio: 50; Size: 25; Frame Size: 25
Allowable Average Torque	72	N·m	Frame Size: 25; Reduction Ratio: 50; Size: 25
Angular Transmission Accuracy	1	arcmin	Frame Size: 25; Reduction Ratio: 50; Size: 25
Hysteresis Loss	2	arcmin	Frame Size: 25; Reduction Ratio: 50; Size: 25
MECHANICAL			
Frame Size	25		Frame Size: 25; Reduction Ratio: 50; Size: 25
Weight	2.02	kg	Frame Size: 25; Reduction Ratio: 50; Size: 25

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
RELIABILITY			
Design Life	10000	h	Frame Size: 25; Reduction Ratio: 50; Size: 25
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	50		Frame Size: 25; Reduction Ratio: 50; Size: 25
Maximum Input Speed	5600	r/min	Frame Size: 25; Reduction Ratio: 50; Size: 25
Average Input Speed	3500	r/min	Frame Size: 25; Reduction Ratio: 50; Size: 25
Torsional Rigidity K2	3.4	$\times 10^4$ N·m/rad	Frame Size: 25; Reduction Ratio: 50; Size: 25
Torsional Rigidity K1	2.5	$\times 10^4$ N·m/rad	Frame Size: 25; Reduction Ratio: 50; Size: 25
Torsional Rigidity K3	4.4	$\times 10^4$ N·m/rad	Frame Size: 25; Reduction Ratio: 50; Size: 25
Torsional Rigidity T2	48	N·m	Frame Size: 25; Reduction Ratio: 50; Size: 25
Torsional Rigidity T1	14	N·m	Frame Size: 25; Reduction Ratio: 50; Size: 25

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Overall length	55.5 mm
	Middle section length	43.5 mm
	Right section length	6 mm
	Left section length	26 mm
	Lower left section length	10.5 mm
	Right section length	8.5 mm
	Outer mounting hole diameter with tolerance	Φ110 H7
		Φ115 h7
	Inner hole diameter with tolerance (upper right)	Φ29 H7
	Inner hole diameter with tolerance (lower left)	
	Middle hole diameter with tolerance	Φ60 h7
		Φ38 h7
	Middle ring diameter	Φ90
	Center section length	23 mm
	Lower left end length	10 mm

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 2	Flange mounting threaded holes	6 × M3 threaded holes
	Pitch circle diameter of mounting holes	DP6 (likely designation or reference code)
	Center bore diameter	φ33.5 mm
	Outer mounting holes	12 × φ4.5 mm holes
	Flange outer diameter	φ102 mm
Mechanical View 3	Outer circle threaded holes (M4)	16 holes, M4 thread, tap depth 8 mm
	Outer circle through holes (Φ4.5)	16 holes, Φ4.5 mm, through depth 15.5 mm
	Outer circle diameter	Φ77 mm
	Inner circle diameter	Φ33.5 mm
	Inner circle threaded holes (M3)	6 holes, M3 thread, tap depth 6 mm

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.