PRODUCT DATASHEET

ES-HG-S28-F14-R50

Precision Transmission Component

Ultra-Thin Harmonic Gearboxes | Ultra-Short Hollow Shaft Gear Unit

Product Overview

Precision Transmission Component with rated Torque 3.7 N·m, instantaneous Maximum Torque 24 N·m and start/Stop Peak Torque 12 N·m.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	3.7	N·m
Instantaneous Maximum Torque	24	N·m
Start/Stop Peak Torque	12	N·m
Reduction Ratio	50	
Maximum Input Speed	8500	r/min
Allowable Average Torque	4.8	N·m
Frame Size	14	
Weight	0.64	kg
Average Input Speed	3500	r/min

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	3.7	N·m	Frame Size: 14; Reduction Ratio: 50; Size: 14
Instantaneous Maximum Torque	24	N·m	Frame Size: 14; Reduction Ratio: 50
Start/Stop Peak Torque	12	N·m	Frame Size: 14; Reduction Ratio: 50; Size: 14
Allowable Average Torque	4.8	N·m	Frame Size: 14; Reduction Ratio: 50; Size: 14
Angle Transmission Accuracy	1.5	arc min	Frame Size: 14; Ratio Bucket: 50; Reduction Ratio: 50; Size: 14
Hysteresis Loss	2.5	arc min	Frame Size: 14; Ratio Bucket: 50; Reduction Ratio: 50; Size: 14
MECHANICAL			
Frame Size	14		Frame Size: 14; Reduction Ratio: 50; Size: 14
Weight	0.64	kg	Frame Size: 14; Reduction Ratio: 50; Size: 14
RELIABILITY			
Design Life	9000	h	Frame Size: 14; Reduction Ratio: 50; Size: 14

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	50		Frame Size: 14; Reduction Ratio: 50; Size: 14
Maximum Input Speed	8500	r/min	Frame Size: 14; Reduction Ratio: 50; Size: 14
Average Input Speed	3500	r/min	Frame Size: 14; Reduction Ratio: 50; Size: 14
Torsional Rigidity K2	0.23	$\times 10^4$ N·m/rad	Frame Size: 14; Ratio Bucket: 50; Reduction Ratio: 50; Size: 14; Source Condition: ratio=50
Torsional Rigidity K1	0.19	$\times 10^4$ N·m/rad	Frame Size: 14; Ratio Bucket: 50; Reduction Ratio: 50; Size: 14; Source Condition: ratio=50
Torsional Rigidity K3	0.27	$\times 10^4$ N·m/rad	Frame Size: 14; Ratio Bucket: 50; Reduction Ratio: 50; Size: 14; Source Condition: ratio=50
Torsional Rigidity T2	2	N·m	Frame Size: 14; Ratio Bucket: 50; Reduction Ratio: 50; Size: 14; Source Condition: all ratios
Torsional Rigidity T1	0.8	N·m	Frame Size: 14; Ratio Bucket: 50; Reduction Ratio: 50; Size: 14; Source Condition: all ratios

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	14	
Weight	0.64	kg

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.