PRODUCT DATASHEET

ES-HG-S29-F11-R100

Precision Transmission Component

Ultra-Thin Harmonic Gearboxes | Ultra-Short Gear Unit

Product Overview

Precision Transmission Component with rated Torque 3.5 N·m, instantaneous Maximum Torque 17.5 N·m and start/Stop Peak Torque 7.7 N·m.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	3.5	N·m
Instantaneous Maximum Torque	17.5	N·m
Start/Stop Peak Torque	7.7	N·m
Reduction Ratio	100	
Maximum Input Speed	8000	r/min
Allowable Average Torque	6.2	N·m
Frame Size	11	
Weight	0.13	kg
Average Input Speed	3500	r/min

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Torque	3.5	N·m	Frame Size: 11; Reduction Ratio: 100; Size: 11
Instantaneous Maximum Torque	17.5	N·m	Frame Size: 11; Reduction Ratio: 100; Size: 11
Start/Stop Peak Torque	7.7	N·m	Frame Size: 11; Reduction Ratio: 100; Size: 11
Allowable Average Torque	6.2	N·m	Frame Size: 11; Reduction Ratio: 100; Size: 11
Angle Transmission Accuracy	2	arc min	Frame Size: 11; Ratio Bucket: >50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 11
Hysteresis Loss	2.5	arc min	Frame Size: 11; Ratio Bucket: >50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 11
MECHANICAL			
Frame Size	11		Frame Size: 11; Reduction Ratio: 100; Size: 11
Weight	0.13	kg	Frame Size: 11; Reduction Ratio: 100; Size: 11
Wave Generator Bore U	φ6H7 / φ5H7		Frame Size: 11; Option Index: 1; Option Label: Wave generator - A φ 6; Reduction Ratio: 100; Wave Generator Option: wave-generator-4df7ad827c47 / Frame Size: 11; Option Label: Wave generator - A φ 5; Reduction Ratio: 100; Wave Generator Option: wave-generator-9b68021d3e2c

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
RELIABILITY			
Design Life	8000	h	Frame Size: 11; Reduction Ratio: 100; Size: 11
ADDITIONAL SPECIFICATIONS			
Reduction Ratio	100		Frame Size: 11; Reduction Ratio: 100; Size: 11
Maximum Input Speed	8000	r/min	Frame Size: 11; Reduction Ratio: 100; Size: 11
Average Input Speed	3500	r/min	Frame Size: 11; Reduction Ratio: 100; Size: 11
Torsional Rigidity K2	0.077	$\times 10^4$ N·m/rad	Frame Size: 11; Ratio Bucket: >50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 11; Source Condition: ratio>50
Torsional Rigidity K1	0.073	$\times 10^4$ N·m/rad	Frame Size: 11; Ratio Bucket: >50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 11; Source Condition: ratio>50
Torsional Rigidity K3	0.1	$\times 10^4$ N·m/rad	Frame Size: 11; Ratio Bucket: >50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 11; Source Condition: ratio>50
Torsional Rigidity T2	0.75	N·m	Frame Size: 11; Ratio Bucket: >50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 11; Source Condition: all ratios
Torsional Rigidity T1	0.29	N·m	Frame Size: 11; Ratio Bucket: >50; Reduction Ratio: 100; Reduction Ratio Min: 50; Size: 11; Source Condition: all ratios

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	11	
Weight	0.13	kg
Wave Generator Bore U	φ6H7 / φ5H7	

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.