

PRODUCT DATASHEET

ES-PG-C36-S006-V012

Precision Transmission Component

Ultra-Precision Planetary Gearboxes | Ultra-Precision Planetary Gearbox Series - ES-PG-C36-S006

Product Overview

Precision Transmission Component with backlash 7 / 5 arcmin, maximum Input Speed 6000 rpm and frame Size 64 mm.

Key Specifications

PARAMETER	VALUE	UNIT
Backlash	7 / 5	arcmin
Maximum Input Speed	6000	rpm
Frame Size	64	mm
Weight	1.6	kg
Compatible Servo Motor Power	400	W
Motor Adapter Interface	T1	
Rated Output Torque	48 / 40	Nm
Number of Reduction Stages	2	
A-Weighted Noise Level	58	dB(A)

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Backlash	7 / 5	arcmin	Precision Grade: P2; Reduction Ratio: 15~100 / Precision Grade: P1; Reduction Ratio: 15~100
Rated Output Torque	48 / 40	Nm	Reduction Ratio: 20 / Reduction Ratio: 100
Rated Input Speed	3000	rpm	Reduction Ratio: 4~100
Torsional Rigidity	13	Nm/ar cmin	Reduction Ratio: 4~100
Permissible Axial Load	1050	N	Reduction Ratio: 4~100
Maximum Bending Moment	125	Nm	Reduction Ratio: 4~100
MECHANICAL			
Frame Size	64	mm	
Weight	1.6	kg	Reduction Ratio: 15~100
ENVIRONMENTAL			
A-Weighted Noise Level	58	dB(A)	Reduction Ratio: 4~100
ADDITIONAL SPECIFICATIONS			
Maximum Input Speed	6000	rpm	Reduction Ratio: 4~100
Compatible Servo Motor Power	400	W	
Motor Adapter Interface	T1		
Number of Reduction Stages	2		

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	64	mm
Weight	1.6	kg

[View Product Online](#)[Request Engineering Data](#)[Request a Quote](#)

- 01

Specifications are subject to change without notice. Verify the current product configuration before final design release.
- 02

2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.