PRODUCT DATASHEET

ES-PG-C36-S006-V027

Precision Transmission Component

Ultra-Precision Planetary Gearboxes | Ultra-Precision Planetary Gearbox Series - ES-PG-C36-S006

Product Overview

Precision Transmission Component with backlash 7 / 5 arcmin, maximum Input Speed 6000 rpm and frame Size 90 mm.

Key Specifications

PARAMETER	VALUE	UNIT
Backlash	7 / 5	arcmin
Maximum Input Speed	6000	rpm
Frame Size	90	mm
Weight	3.7	kg
Compatible Servo Motor Power	1000	W
Motor Adapter Interface	T4	
Rated Output Torque	100	N·m
Number of Reduction Stages	2	
A-Weighted Noise Level	60	dB(A)

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Backlash	7 / 5	arcmin	Precision Grade: P2; Reduction Ratio: 15~100 / Precision Grade: P1; Reduction Ratio: 15~100
Rated Output Torque	100	N·m	Reduction Ratio: 100
Rated Input Speed	3000	rpm	Reduction Ratio: 4~100
Torsional Rigidity	31	N·m/arcmin	Reduction Ratio: 4~100
Permissible Axial Load	2850	N	Reduction Ratio: 4~100
Maximum Bending Moment	235	N·m	Reduction Ratio: 4~100
MECHANICAL			
Frame Size	90	mm	
Weight	3.7	kg	Reduction Ratio: 15~100
ENVIRONMENTAL			
A-Weighted Noise Level	60	dB(A)	Reduction Ratio: 4~100
ADDITIONAL SPECIFICATIONS			
Maximum Input Speed	6000	rpm	Reduction Ratio: 4~100
Compatible Servo Motor Power	1000	W	
Motor Adapter Interface	T4		
Number of Reduction Stages	2		

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	90	mm
Weight	3.7	kg

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.