

PRODUCT DATASHEET

ES-PG-C36-S009-V082

Precision Transmission Component

Ultra-Precision Planetary Gearboxes | Ultra-Precision Planetary Gearbox Series - ES-PG-C36-S009

Product Overview

Precision Transmission Component with backlash 7 / 1 arcmin, maximum Input Speed 6000 rpm and frame Size 115 mm.

Key Specifications

PARAMETER	VALUE	UNIT
Backlash	7 / 1	arcmin
Maximum Input Speed	6000	rpm
Frame Size	115	mm
Weight	9 / 7.8	kg
Compatible Servo Motor Power	1000	W
Motor Adapter Interface	T1	
A-Weighted Noise Level	63	dB(A)
Permissible Axial Load	3350	N
Permissible Radial Load	6700	N

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Backlash	7 / 1	arcmin	Precision Grade: P2; Reduction Ratio: 15 100; Stage: 2 / Precision Grade: P0; Reduction Ratio: 3 10; Stage: 1
Rated Input Speed	3000	rpm	Reduction Ratio: 3 100; Stage: 2
Torsional Rigidity	25	Nm/arcmin	Reduction Ratio: 3 100; Stage: 2
Permissible Axial Load	3350	N	Reduction Ratio: 3 100; Stage: 2
Permissible Radial Load	6700	N	Reduction Ratio: 3 100; Stage: 2
MECHANICAL			
Frame Size	115	mm	
Weight	9 / 7.8	kg	Reduction Ratio: 15 100; Stage: 2 / Reduction Ratio: 3 10; Stage: 1
ENVIRONMENTAL			
A-Weighted Noise Level	63	dB(A)	Reduction Ratio: 3 100; Stage: 2
ADDITIONAL SPECIFICATIONS			
Maximum Input Speed	6000	rpm	Reduction Ratio: 3 100; Stage: 2
Compatible Servo Motor Power	1000	W	
Motor Adapter Interface	T1		

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	115	mm
Weight	9 / 7.8	kg

[View Product Online](#)[Request Engineering Data](#)[Request a Quote](#)

- 01

Specifications are subject to change without notice. Verify the current product configuration before final design release.
- 02

2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.