PRODUCT DATASHEET

ES-PG-C36-S015-V003

Precision Transmission Component

Ultra-Precision Planetary Gearboxes | Ultra-Precision Planetary Gearbox Series - ES-PG-C36-S015

Product Overview

Precision Transmission Component with backlash 7 / 5 arcmin, maximum Input Speed 6000 rpm and frame Size 70 mm.

Key Specifications

PARAMETER	VALUE	UNIT
Backlash	7 / 5	arcmin
Maximum Input Speed	6000	rpm
Frame Size	70	mm
Weight	1.6	kg
Compatible Servo Motor Power	400	W
Motor Adapter Interface	T3	
Number of Reduction Stages	2	
A-Weighted Noise Level	58	dB(A)
Permissible Axial Load	765	N

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Backlash	7 / 5	arcmin	Precision Grade: P2; Reduction Ratio: 15~100 / Precision Grade: P1; Reduction Ratio: 15~100
Rated Input Speed	3000	rpm	Reduction Ratio: 3~100
Torsional Rigidity	7	N·m/arcmin	Reduction Ratio: 3~100
Permissible Axial Load	765	N	Reduction Ratio: 3~100
Permissible Radial Load	1377	N	Reduction Ratio: 3~100
MECHANICAL			
Frame Size	70	mm	
Weight	1.6	kg	Reduction Ratio: 15~100
ENVIRONMENTAL			
A-Weighted Noise Level	58	dB(A)	Reduction Ratio: 3~100
ADDITIONAL SPECIFICATIONS			
Maximum Input Speed	6000	rpm	Reduction Ratio: 3~100
Compatible Servo Motor Power	400	W	
Motor Adapter Interface	T3		
Number of Reduction Stages	2		

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	70	mm
Weight	1.6	kg

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.