

## PRODUCT DATASHEET

# ES-PS-C32-S001-V023

## Precision Linear Motion Assembly

Standard Planetary Roller Screws | Standard Planetary Roller Screw Series

### Product Overview

Precision Linear Motion Assembly with nominal diameter 27 mm, ball Screw Lead 10 mm and rated dynamic load  $C_a$  97 kN.

### Key Specifications

| PARAMETER                              | VALUE | UNIT  |
|----------------------------------------|-------|-------|
| Nominal diameter                       | 27    | mm    |
| Ball Screw Lead                        | 10    | mm    |
| Rated dynamic load $C_a$               | 97    | kN    |
| Rated static load $C_{0a}$             | 150   | kN    |
| Maximum dynamic load $C_a$             | 103   | kN    |
| Maximum static load $C_{0a}$           | 175   | kN    |
| Forward theoretical efficiency $\eta$  | 0.89  | ratio |
| Reverse theoretical efficiency $\eta'$ | 0.88  | ratio |
| Body diameter D                        | 55    | mm    |

## Technical Specifications

| PARAMETER                              | SPECIFICATION    | UNIT  |
|----------------------------------------|------------------|-------|
| PERFORMANCE                            |                  |       |
| Rated dynamic load $C_a$               | 97               | kN    |
| Rated static load $C_{0a}$             | 150              | kN    |
| Maximum dynamic load $C_a$             | 103              | kN    |
| Maximum static load $C_{0a}$           | 175              | kN    |
| MECHANICAL                             |                  |       |
| Nominal diameter                       | 27               | mm    |
| Ball Screw Lead                        | 10               | mm    |
| CONFIGURATION                          |                  |       |
| Development status                     | Standard listing |       |
| ADDITIONAL SPECIFICATIONS              |                  |       |
| Forward theoretical efficiency $\eta$  | 0.89             | ratio |
| Reverse theoretical efficiency $\eta'$ | 0.88             | ratio |
| Body diameter D                        | 55               | mm    |

## Technical Specifications


| PARAMETER                     | SPECIFICATION | UNIT |
|-------------------------------|---------------|------|
| ADDITIONAL SPECIFICATIONS     |               |      |
| Overall length W              | 79            | mm   |
| Thread count N                | 5             |      |
| Segment length W <sub>1</sub> | 25.5          | mm   |
| Diameter d <sub>0</sub>       | 27            | mm   |
| Overall height H              | 57.5          | mm   |
| Segment length W <sub>2</sub> | 28            | mm   |
| Diameter d <sub>1</sub>       | 27.7          | mm   |
| Diameter d <sub>2</sub>       | 26            | mm   |
| Segment length W <sub>3</sub> | 39.5          | mm   |

## Dimensional & Integration Overview


### Mechanical Overview

| PARAMETER                     | VALUE | UNIT |
|-------------------------------|-------|------|
| Nominal diameter              | 27    | mm   |
| Ball Screw Lead               | 10    | mm   |
| Body diameter D               | 55    | mm   |
| Overall length W              | 79    | mm   |
| Segment length W <sub>1</sub> | 25.5  | mm   |
| Diameter d <sub>0</sub>       | 27    | mm   |

### Dimensional Drawings



Mechanical View 1



Mechanical View 2

## 2D Drawing Dimensions & Callouts

| VIEW              | FIELD                                    | VALUE                  |
|-------------------|------------------------------------------|------------------------|
| Mechanical View 1 | Overall length W                         | W                      |
|                   | Segment length W2                        | W2                     |
|                   | Segment length W1                        | W1                     |
|                   | Shaft diameters d1, d0 and d2            | d1; d0; d2             |
|                   | Body diameter D                          | D                      |
|                   | Slot or keyway width Q                   | Q                      |
|                   | Lower segment length W3                  | W3                     |
| Mechanical View 2 | Mounting hole pattern pitch/width symbol | b, value Not specified |
|                   | Overall height                           | H, value Not specified |

[View Product Online](#)[Request Engineering Data](#)[Request a Quote](#)

**01** Specifications are subject to change without notice. Verify the current product configuration before final design release.

**02** 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.