PRODUCT DATASHEET

ES-PS-C32-S001-V122

Precision Linear Motion Assembly

Standard Planetary Roller Screws | Standard Planetary Roller Screw Series

Product Overview

Precision Linear Motion Assembly with nominal diameter 48 mm, ball Screw Lead 24 mm and rated dynamic load C_a 248 kN.

Key Specifications

PARAMETER	VALUE	UNIT
Nominal diameter	48	mm
Ball Screw Lead	24	mm
Rated dynamic load C_a	248	kN
Rated static load C_{oa}	429	kN
Maximum dynamic load C_a	262	kN
Maximum static load C_{oa}	465	kN
Forward theoretical efficiency η	0.89	ratio
Reverse theoretical efficiency η´	0.87	ratio
Body diameter D	88	mm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated dynamic load C_a	248	kN
Rated static load C_{oa}	429	kN
Maximum dynamic load C_a	262	kN
Maximum static load C_{oa}	465	kN
MECHANICAL		
Nominal diameter	48	mm
Ball Screw Lead	24	mm
Interface thread Q	M8×1	
Mounting hole pattern G	6×φ11	
CONFIGURATION		
Development status	Standard listing	
ADDITIONAL SPECIFICATIONS		
Forward theoretical efficiency η	0.89	ratio

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ADDITIONAL SPECIFICATIONS		
Reverse theoretical efficiency η′	0.87	ratio
Body diameter D	88	mm
Overall length W	99	mm
Thread count N	6	
Segment length W_1	32	mm
Diameter d_0	48	mm
Segment length W_2	35	mm
Angle α	30	°
Diameter d_1	49.2	mm
Diameter d_2	46	mm

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Nominal diameter	48	mm
Ball Screw Lead	24	mm
Interface thread Q	M8×1	
Mounting hole pattern G	6×φ11	
Body diameter D	88	mm
Overall length W	99	mm

Dimensional Drawings



Mechanical View 1



Mechanical View 2

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Overall length W	W
	Segment length W2	W2
	Segment length W1	W1
	Shaft diameters d1, d0 and d2	d1; d0; d2
	Body diameter D	D
	Slot or keyway width Q	Q
	Lower segment length W3	W3
Mechanical View 2	Mounting hole pattern pitch/width symbol	b, value Not specified
	Overall height	H, value Not specified

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.