PRODUCT DATASHEET

ES-PS-C32-S001-V127

Precision Linear Motion Assembly

Standard Planetary Roller Screws | Standard Planetary Roller Screw Series

Product Overview

Precision Linear Motion Assembly with nominal diameter 56 mm, ball Screw Lead 24 mm and rated dynamic load C_a 293 kN.

Key Specifications

PARAMETER	VALUE	UNIT
Nominal diameter	56	mm
Ball Screw Lead	24	mm
Rated dynamic load C_a	293	kN
Rated static load C_{oa}	530	kN
Maximum dynamic load C_a	310	kN
Maximum static load C_{oa}	574	kN
Forward theoretical efficiency η	0.89	ratio
Reverse theoretical efficiency η´	0.88	ratio
Body diameter D	100	mm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated dynamic load C_a	293	kN
Rated static load C_{oa}	530	kN
Maximum dynamic load C_a	310	kN
Maximum static load C_{oa}	574	kN
MECHANICAL		
Nominal diameter	56	mm
Ball Screw Lead	24	mm
Interface thread Q	M8×1	
Mounting hole pattern G	6×φ13.5	
CONFIGURATION		
Development status	Standard listing	
ADDITIONAL SPECIFICATIONS		
Forward theoretical efficiency η	0.89	ratio

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ADDITIONAL SPECIFICATIONS		
Reverse theoretical efficiency η′	0.88	ratio
Body diameter D	100	mm
Overall length W	112	mm
Thread count N	6	
Segment length W_1	37.5	mm
Diameter d_0	56	mm
Segment length W_2	37	mm
Angle α	30	°
Diameter d_1	57.4	mm
Diameter d_2	54	mm

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Nominal diameter	56	mm
Ball Screw Lead	24	mm
Interface thread Q	M8×1	
Mounting hole pattern G	6×φ13.5	
Body diameter D	100	mm
Overall length W	112	mm

Dimensional Drawings



Mechanical View 1



Mechanical View 2

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Overall length W	W
	Segment length W2	W2
	Segment length W1	W1
	Shaft diameters d1, d0 and d2	d1; d0; d2
	Body diameter D	D
	Slot or keyway width Q	Q
	Lower segment length W3	W3
Mechanical View 2	Mounting hole pattern pitch/width symbol	b, value Not specified
	Overall height	H, value Not specified

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.