

PRODUCT DATASHEET

ES-RD-C36-S001-V023

Precision Transmission Component

Ultra-Precision Planetary Gearboxes | Ultra-Precision Planetary Gearbox Series - ES-RD-C36-S001

Product Overview

Precision Transmission Component with reduction Ratio 15, frame Size 125 mm and compatible Servo Motor Power 2000 W.

Key Specifications

PARAMETER	VALUE	UNIT
Reduction Ratio	15	
Frame Size	125	mm
Compatible Servo Motor Power	2000	W
Rated Output Torque	81	N·m
Number of Reduction Stages	2	
Input-shaft Equivalent Inertia	2.8	x10 ⁻⁴ kg.m ²
Instantaneous Maximum Output Torque	243	N·m
Instantaneous Maximum Permissible Output Torque	274	N·m
Output Shaft Speed	200	rpm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Output Torque	81	N·m
Instantaneous Maximum Output Torque	243	N·m
Instantaneous Maximum Permissible Output Torque	274	N·m
Output Shaft Speed	200	rpm
Permissible Output Torque	91.4	N·m
Permissible Axial Load	1180	N
Permissible Radial Load	2350	N
MECHANICAL		
Frame Size	125	mm
Input-shaft Equivalent Inertia	2.8	$\times 10^{-4}$ kg·m ²
CONFIGURATION		
Reduction Ratio	15	
ADDITIONAL SPECIFICATIONS		
Compatible Servo Motor Power	2000	W
Number of Reduction Stages	2	

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	125	mm
Input-shaft Equivalent Inertia	2.8	$\times 10^{-4}$ kg.m ²

[View Product Online](#)[Request Engineering Data](#)[Request a Quote](#)

- 01

Specifications are subject to change without notice. Verify the current product configuration before final design release.
- 02

2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.