

PRODUCT DATASHEET

ES-RD-C36-S001-V046

Precision Transmission Component

Ultra-Precision Planetary Gearboxes | Ultra-Precision Planetary Gearbox Series - ES-RD-C36-S001

Product Overview

Precision Transmission Component with reduction Ratio 3, 5, frame Size 78 mm and compatible Servo Motor Power 750 W.

Key Specifications

PARAMETER	VALUE	UNIT
Reduction Ratio	3, 5	
Frame Size	78	mm
Compatible Servo Motor Power	750	W
Rated Output Torque	6.37 / 10.7	N·m
Number of Reduction Stages	1	
Input-shaft Equivalent Inertia	0.913 / 0.713	x10 ⁻⁴ kg.m ²
Instantaneous Maximum Output Torque	19.3 / 32.1	N·m
Instantaneous Maximum Permissible Output Torque	20.6 / 34.3	N·m
Output Shaft Speed	600 / 1000	rpm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Rated Output Torque	6.37 / 10.7	Nm	Reduction Ratio: 3 / Reduction Ratio: 5
Instantaneous Maximum Output Torque	19.3 / 32.1	Nm	Reduction Ratio: 3 / Reduction Ratio: 5
Instantaneous Maximum Permissible Output Torque	20.6 / 34.3	Nm	Reduction Ratio: 3 / Reduction Ratio: 5
Output Shaft Speed	600 / 1000	rpm	Reduction Ratio: 5 / Reduction Ratio: 3
Permissible Output Torque	6.86 / 11.5	Nm	Reduction Ratio: 3 / Reduction Ratio: 5
Permissible Axial Load	490 / 392	N	Reduction Ratio: 5 / Reduction Ratio: 3
Permissible Radial Load	784 / 980	N	Reduction Ratio: 3 / Reduction Ratio: 5
MECHANICAL			
Frame Size	78	mm	
Input-shaft Equivalent Inertia	0.913 / 0.713	$\times 10^{-4}$ kg.m ²	Reduction Ratio: 3 / Reduction Ratio: 5
CONFIGURATION			
Reduction Ratio	3, 5		
ADDITIONAL SPECIFICATIONS			
Compatible Servo Motor Power	750	W	
Number of Reduction Stages	1		

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	78	mm
Input-shaft Equivalent Inertia	0.913 / 0.713	$\times 10^{-4}$ kg.m ²

[View Product Online](#)[Request Engineering Data](#)[Request a Quote](#)

- 01

Specifications are subject to change without notice. Verify the current product configuration before final design release.
- 02

2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.