

PRODUCT DATASHEET

ES-RD-C36-S001-V047

Precision Transmission Component

Ultra-Precision Planetary Gearboxes | Ultra-Precision Planetary Gearbox Series - ES-RD-C36-S001

Product Overview

Precision Transmission Component with reduction Ratio 35, frame Size 78 mm and compatible Servo Motor Power 100 W.

Key Specifications

PARAMETER	VALUE	UNIT
Reduction Ratio	35	
Frame Size	78	mm
Compatible Servo Motor Power	100	W
Rated Output Torque	7.24	N·m
Number of Reduction Stages	2	
Input-shaft Equivalent Inertia	0.065	$\times 10^{-4}$ kg.m ²
Instantaneous Maximum Output Torque	21.7	N·m
Instantaneous Maximum Permissible Output Torque	41.7	N·m
Output Shaft Speed	85	rpm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Output Torque	7.24	N·m
Instantaneous Maximum Output Torque	21.7	N·m
Instantaneous Maximum Permissible Output Torque	41.7	N·m
Output Shaft Speed	85	rpm
Permissible Output Torque	13.9	N·m
Permissible Axial Load	833	N
Permissible Radial Load	1670	N
MECHANICAL		
Frame Size	78	mm
Input-shaft Equivalent Inertia	0.065	$\times 10^{-4}$ kg·m ²
CONFIGURATION		
Reduction Ratio	35	
ADDITIONAL SPECIFICATIONS		
Compatible Servo Motor Power	100	W
Number of Reduction Stages	2	

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	78	mm
Input-shaft Equivalent Inertia	0.065	$\times 10^{-4}$ kg.m ²

[View Product Online](#)[Request Engineering Data](#)[Request a Quote](#)

- 01

Specifications are subject to change without notice. Verify the current product configuration before final design release.
- 02

2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.