

PRODUCT DATASHEET

ES-RD-C36-S001-V056

Precision Transmission Component

Ultra-Precision Planetary Gearboxes | Ultra-Precision Planetary Gearbox Series - ES-RD-C36-S001

Product Overview

Precision Transmission Component with reduction Ratio 35, frame Size 98 mm and compatible Servo Motor Power 400 W.

Key Specifications

PARAMETER	VALUE	UNIT
Reduction Ratio	35	
Frame Size	98	mm
Compatible Servo Motor Power	400	W
Rated Output Torque	37	N·m
Number of Reduction Stages	2	
Input-shaft Equivalent Inertia	0.269	$\times 10^{-4}$ kg.m ²
Instantaneous Maximum Output Torque	111	N·m
Instantaneous Maximum Permissible Output Torque	111	N·m
Output Shaft Speed	85	rpm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Output Torque	37	N·m
Instantaneous Maximum Output Torque	111	N·m
Instantaneous Maximum Permissible Output Torque	111	N·m
Output Shaft Speed	85	rpm
Permissible Output Torque	37	N·m
Permissible Axial Load	1030	N
Permissible Radial Load	2060	N
MECHANICAL		
Frame Size	98	mm
Input-shaft Equivalent Inertia	0.269	$\times 10^{-4}$ kg·m ²
CONFIGURATION		
Reduction Ratio	35	
ADDITIONAL SPECIFICATIONS		
Compatible Servo Motor Power	400	W
Number of Reduction Stages	2	

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Frame Size	98	mm
Input-shaft Equivalent Inertia	0.269	$\times 10^{-4}$ kg.m ²

[View Product Online](#)[Request Engineering Data](#)[Request a Quote](#)

- 01

Specifications are subject to change without notice. Verify the current product configuration before final design release.
- 02

2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.