

PRODUCT DATASHEET

ES-SD-C21-S003-V008

Industrial Motion Controller

Medium Power Servo Drives | Medium-Power Servo Drive Series - ES-SD-C21-S003

Product Overview

Industrial Motion Controller with logic Supply Voltage 1PH 200VAC-240VAC $\pm$ 10%50/60Hz $\pm$ 3Hz, peak Output Current A / 32.53 A and communication Protocol RS232; EtherCAT; CoE CiA 402; Pulse train.

Key Specifications

PARAMETER	VALUE	UNIT
Logic Supply Voltage	1PH 200VAC-240VAC $\pm$ 10%50/60Hz $\pm$ 3Hz	
Peak Output Current	A / 32.53	A
Communication Protocol	RS232; EtherCAT; CoE CiA 402; Pulse train	
Weight	kg / 2.1	kg
Cooling Method	Forced-air cooling	
Braking Resistor	Integrated braking resistor, 50 Ω , 80 W limited power	
Rated Output Power	W / 2500	W
Servo Drive AC Supply Voltage	3-phase 200-240 VAC $\pm$ 10%, 50/60 Hz $\pm$ 3 Hz	
Atmospheric Pressure	86-106 kPa	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ELECTRICAL		
Logic Supply Voltage	1PH 200VAC-240VAC $\pm$ 10%50/60Hz $\pm$ 3Hz	
Peak Output Current	A / 32.53	A
Braking Resistor	Integrated braking resistor, 50 Ω , 80 W limited power	
Servo Drive AC Supply Voltage	3-phase 200-240 VAC $\pm$ 10%, 50/60 Hz $\pm$ 3 Hz	
Protection Functions	Overvoltage, undervoltage, motor I ² T overtemperature, short-circuit and drive overtemperature protection	
Rated Output Power	W / 2500	W
Overvoltage Alarm Voltage	400 $\pm$ 5	V DC
Undervoltage Alarm Voltage	200 $\pm$ 5	V DC
Braking Absorption Voltage	380 $\pm$ 5	V DC
MECHANICAL		
Weight	kg / 2.1	kg
INTERFACES		
Communication Protocol	RS232; EtherCAT; CoE CiA 402; Pulse train	
Position-loop sampling frequency	8	kHz

Technical Specifications


PARAMETER	SPECIFICATION	UNIT
INTERFACES		
Speed-loop sampling frequency	16	kHz
Current-loop sampling frequency	16	kHz
ENVIRONMENTAL		
Cooling Method	Forced-air cooling	
Atmospheric Pressure	86-106 kPa	
Operating Temperature	0-40	°C
Relative humidity	5-95	% RH
Storage Temperature	-10 °C-70 °C	
SAFETY		
STO Support	No / false	
ADDITIONAL SPECIFICATIONS		
Continuous output current	13	A
Protection rating	IP20 enclosure; connection terminals IP00	
Supply voltage	3-phase 200-240 VAC ±10%, 50/60 Hz ±3 Hz	

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Weight	kg / 2.1	kg

Dimensional Drawings




Mechanical View 1



Mechanical View 2



Mechanical View 3



Mechanical View 4



Mechanical View 5

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Left body height	173.8 mm
	Right assembly height	168.64 mm
	Optional battery-box area label	Optional area for battery box
	Optional battery-box area height	25.00 mm
	Main body length	186.00 mm
Mechanical View 3	Fixation hole diameter and quantity	2 holes, diameter 5.35 mm
	Upper right hole horizontal edge offset	5.15 mm horizontal offset
	Upper right hole vertical edge offset	4.15 mm vertical offset
	Overall fixation hole position height	162.00 mm
	Lower left hole horizontal edge offset	5.35 mm horizontal offset
	Overall fixation hole position width	75.15 mm
	Fixation hole position note	Hole position for fixation
Mechanical View 4	Front view width	Width 80.30 mm

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.