

PRODUCT DATASHEET

ES-SD-C21-S003-V010

Industrial Motion Controller

Medium Power Servo Drives | Medium-Power Servo Drive Series - ES-SD-C21-S003

Product Overview

Industrial Motion Controller with logic Supply Voltage No separate logic supply recorded V DC, peak Output Current A / 16.97 A and communication Protocol RS232; EtherCAT; CoE CiA 402; Pulse train.

Key Specifications

PARAMETER	VALUE	UNIT
Logic Supply Voltage	No separate logic supply recorded	V DC
Peak Output Current	A / 16.97	A
Communication Protocol	RS232; EtherCAT; CoE CiA 402; Pulse train	
Weight	kg / 1.5	kg
Cooling Method	Forced-air cooling	
Braking Resistor	No integrated braking resistor	
Rated Output Power	W / 1000	W
Servo Drive AC Supply Voltage	1-phase 200-240 VAC $\pm 10\%$, 50/60 Hz ± 3 Hz	
Atmospheric Pressure	86-106 kPa	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ELECTRICAL		
Logic Supply Voltage	No separate logic supply recorded	V DC
Peak Output Current	A / 16.97	A
Braking Resistor	No integrated braking resistor	
Servo Drive AC Supply Voltage	1-phase 200-240 VAC $\pm 10\%$, 50/60 Hz ± 3 Hz	
Protection Functions	Overvoltage, undervoltage, motor I ² T overtemperature, short-circuit and drive overtemperature protection	
Rated Output Power	W / 1000	W
Overvoltage Alarm Voltage	400 $\pm$ 5	V DC
Undervoltage Alarm Voltage	200 $\pm$ 5	V DC
Braking Absorption Voltage	380 $\pm$ 5	V DC
MECHANICAL		
Weight	kg / 1.5	kg
INTERFACES		
Communication Protocol	RS232; EtherCAT; CoE CiA 402; Pulse train	
Position-loop sampling frequency	8	kHz

Technical Specifications


PARAMETER	SPECIFICATION	UNIT
INTERFACES		
Speed-loop sampling frequency	16	kHz
Current-loop sampling frequency	16	kHz
ENVIRONMENTAL		
Cooling Method	Forced-air cooling	
Atmospheric Pressure	86-106 kPa	
Operating Temperature	0-40	°C
Relative humidity	5-95	% RH
Storage Temperature	-10 °C-70 °C	
SAFETY		
STO Support	No / false	
ADDITIONAL SPECIFICATIONS		
Continuous output current	5.5	A
Protection rating	IP20 enclosure; connection terminals IP00	
Supply voltage	1-phase 200-240 VAC $\pm 10\%$, 50/60 Hz ± 3 Hz	

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Weight	kg / 1.5	kg

Dimensional Drawings



Mechanical View 1




Mechanical View 2



Mechanical View 3



Mechanical View 4



Mechanical View 5

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Main body overall height	Overall height 170.00 mm
	Main body length	Main body length 153.00 mm
Mechanical View 2	Front panel width	Width 55.00 mm
	Display window placeholder characters	Five-digit seven-segment display placeholder
	Mode button label	MODE button label
	Set button label	SET button label
	Bus indicator label	BUS label
Mechanical View 3	Fixation hole diameter	Diameter 5.5
	Fixation hole horizontal position	17.75 from right-side reference edge to hole centerline
	Fixation hole vertical position	5.75 from top reference edge to hole centerline
	Mounting plate height	Overall height 160.00
	Bottom mounting slot width	Bottom slot width 5.6
	Bottom slot to right reference edge distance	32.00 from bottom slot center/reference line to right-side reference edge
	Descriptive note	Hole position for fixation

[View Product Online](#)
[Request Engineering Data](#)
[Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.