PRODUCT DATASHEET

ES-SD-C21-S003-V014

Industrial Motion Controller

Medium Power Servo Drives | Medium-Power Servo Drive Series - ES-SD-C21-S003

Product Overview

Industrial Motion Controller with logic Supply Voltage 1-phase 380-415 VAC ±10%, 50/60 Hz ±3 Hz, peak Output Current A / 53.04 A and communication Protocol RS232; RS485; Modbus RTU; Pulse train.

Key Specifications

PARAMETER	VALUE	UNIT
Logic Supply Voltage	1-phase 380-415 VAC ±10%, 50/60 Hz ±3 Hz	
Peak Output Current	A / 53.04	A
Communication Protocol	RS232; RS485; Modbus RTU; Pulse train	
Weight	kg / 4	kg
Cooling Method	Forced-air cooling	
Braking Resistor	Integrated braking resistor, 25 Ω, 100 W limited power	
Rated Output Power	W / 5500	W
Servo Drive AC Supply Voltage	3-phase 380-415 VAC ±10%, 50/60 Hz ±3 Hz	
Atmospheric Pressure	86-106 kPa	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ELECTRICAL		
Logic Supply Voltage	1-phase 380-415 VAC ±10%, 50/60 Hz ±3 Hz	
Peak Output Current	A / 53.04	A
Braking Resistor	Integrated braking resistor, 25 Ω, 100 W limited power	
Servo Drive AC Supply Voltage	3-phase 380-415 VAC ±10%, 50/60 Hz ±3 Hz	
Protection Functions	Overvoltage, undervoltage, motor I^2T overtemperature, short-circuit and drive overtemperature protection	
Rated Output Power	W / 5500	W
Overvoltage Alarm Voltage	710 ± 5	V DC
Undervoltage Alarm Voltage	400 ± 5	V DC
Braking Absorption Voltage	680 ± 5	V DC
MECHANICAL		
Weight	kg / 4	kg
INTERFACES		
Communication Protocol	RS232; RS485; Modbus RTU; Pulse train	
Position-loop sampling frequency	8	kHz

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
INTERFACES		
Speed-loop sampling frequency	16	kHz
Current-loop sampling frequency	16	kHz
ENVIRONMENTAL		
Cooling Method	Forced-air cooling	
Atmospheric Pressure	86-106 kPa	
Operating Temperature	0-40	°C
Relative humidity	5-95	% RH
Storage Temperature	-10 °C-70 °C	
SAFETY		
STO Support	No / false	
ADDITIONAL SPECIFICATIONS		
Continuous output current	21	A
Protection rating	IP20 enclosure; connection terminals IP00	
Supply voltage	3-phase 380-415 VAC ±10%, 50/60 Hz ±3 Hz	

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Weight	kg / 4	kg

Dimensional Drawings

Mechanical View 1



Mechanical View 2

Mechanical View 3

Mechanical View 4

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Vertical distance from upper-right hole position to top edge	4.00 mm
	Horizontal positioning distance for upper-left fixation hole	5.25 mm
	Horizontal positioning distance for upper-right fixation hole	5.14 mm
	Vertical spacing of fixation hole positions	239.23 mm
	Horizontal positioning distance for lower-left fixation hole	5.14 mm
	Lower-left slot width or offset distance	5.54 mm
	Horizontal spacing between lower fixation positions	80.00 mm
	View label	Hole position for fixation
Mechanical View 2	Front view width dimension	Width = 90.28 mm
	Display placeholder reading	Display placeholder text: 88888
	Set button label	Button label: SET
	Charge indicator label	Indicator label: CHARGE
	Protective earth terminal label	Protective earth terminal: PE

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.