

PRODUCT DATASHEET

ES-SM-A01-040S-TOP32NM-100W-002

AC Servo Motors


AC Servo Motors | ES-SM-A01-040S Standard 40 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 0.32 N·m, instantaneous Maximum Torque 0.96 N·m and rated Speed 3000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	0.32	N·m
Instantaneous Maximum Torque	0.96	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	100	W
Instantaneous Maximum Current	4.2	A
Flange Size	40	mm
Torque Constant	0.268	N·m/A
Rated Voltage	220	V AC
Rated Line Voltage	220	V



Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	0.32	Nm
Instantaneous Maximum Torque	0.96	Nm
Rated Speed	3000	rpm
Continuous Rated Output Power	100	W
Torque Constant	0.268	Nm/A
Rated Power	100	W
ELECTRICAL		
Rated Voltage	220	V AC
Rated Line Voltage	220	V
Instantaneous Maximum Current	4.2	A
Back EMF Constant	16.2	V/krpm
Insulation Class	F	
Maximum Allowed Voltage Slew Rate	8	KV/ μ s
Motor Outlet Mode	Communication encoder socket	
Pole Pairs	5	
Rated Current	1.4	A

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
ELECTRICAL			
Rotational Back-EMF Constant	16.2	V/krpm	
Electrical Time Constant	1.33	ms	
Position Feedback Device	Single-turn communication magnetic encoder		
MECHANICAL			
Flange Size	40	mm	
Inertia Level	Low inertia		
Holding Brake Available	With holding brake		
Mechanical Time Constant	0.99	ms	Brake Configuration: without_brake
Rotor Inertia	0.046 kg·cm ² / 0.033 Kg·cm ²		Brake Configuration: without_brake
Bearing Radial Force Capacity	120	N	
Bearing Axial Force Capacity	60	N	
ENVIRONMENTAL			
Altitude and Derating Rule	Maximum altitude 4000 m; above 1000 m, power derates 1.5% per 100 m		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		
Operating Temperature	-20 to 40°C (no freezing)		
Protection Rating	IP65, shaft end IP54 (Note: with shaft-end oil seal IP54, without oil seal IP50)		

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Maximum upper protrusion height	15 max
	Mounting hole quantity and diameter	2 holes, diameter 3.5
	Mounting hole angular position	45 degrees
	Mounting face height	40
	Mounting circle diameter	Diameter 45 ±0.2
	Mounting face width	40

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 4	Small shaft end slot length	12 mm, +0/-0.43
	Slot width	3 mm, +0/-0.014
	Slot depth or slot height	
	Small shaft diameter	Diameter 8 mm, +0/-0.013
	Threaded hole size and thread depth	M3 thread, thread depth 8 mm
	Hole depth	Hole depth 10 mm
	Main body diameter	Diameter 30 mm, +0/-0.021
	Small shaft protrusion length	12 mm
	Left end to shoulder length	20.5 mm $\pm$ 0.2
	Shoulder step width	5 mm
	Clearance or shoulder offset dimension	2.8 mm
	Left end to main body datum length	23.8 mm $\pm$ 0.8
	Main body overall length	126.6 mm $\pm$ 1

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.