

PRODUCT DATASHEET

ES-SM-A01-080S-T2P39NM-750W-001

AC Servo Motors


AC Servo Motors | ES-SM-A01-080S Standard 80 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 2.39 N·m, instantaneous Maximum Torque 7.17 N·m and rated Speed 3000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	2.39	N·m
Instantaneous Maximum Torque	7.17	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	750	W
Instantaneous Maximum Current	12.6	A
Flange Size	80	mm
Torque Constant	0.662	N·m/A
Rated Voltage	300	V AC
Rated Line Voltage	300	V



Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	2.39	Nm
Instantaneous Maximum Torque	7.17	Nm
Rated Speed	3000	rpm
Continuous Rated Output Power	750	W
Torque Constant	0.662	Nm/A
ELECTRICAL		
Rated Voltage	300	V AC
Rated Line Voltage	300	V
Instantaneous Maximum Current	12.6	A
Electrical Time Constant	4.63	ms
Insulation Class	F	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
ELECTRICAL			
Maximum Allowed Voltage Slew Rate	8	KV/ μ s	
Motor Outlet Mode	Communication encoder socket		
Pole Pairs	5		
Rated Current	4	A	
Rotational Back-EMF Constant	40	V/krpm	
Position Feedback Device	Single-turn communication magnetic encoder		
MECHANICAL			
Flange Size	80	mm	
Inertia Level	Low inertia		
Holding Brake Available	Without holding brake		
Mechanical Time Constant	0.711	ms	Brake Configuration: without_brake

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Rotor Inertia	1.027 kgcm ² / 1.027 Kg·cm2		Brake Configuration: without_brake
Bearing Radial Force Capacity	335	N	
Bearing Axial Force Capacity	167.5	N	
ENVIRONMENTAL			
Altitude and Derating Rule	Maximum altitude 4000 m; above 1000 m, power derates 1.5% per 100 m		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		
Operating Temperature	-20 to 40°C (no freezing)		
Protection Rating	IP65, shaft end IP54 (Note: with shaft-end oil seal IP54, without oil seal IP50)		
CONFIGURATION			
Output Shaft Type	Keyed shaft		
ADDITIONAL SPECIFICATIONS			
Holding Brake	false		

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	80	mm
Inertia Level	Low inertia	
Holding Brake Available	Without holding brake	
Mechanical Time Constant	0.711	ms
Rotor Inertia	1.027 kgcm ² / 1.027 Kg·cm ²	
Bearing Radial Force Capacity	335	N


Dimensional Drawings




Mechanical View 1



Power Connector Pinout



Mechanical View 3



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Key width	6 mm
	Key height	
	Key length	22 mm
	Key label	Key
	Thread specification	CM6L15
	Pilot diameter	Diameter 70 mm, +0/-0.02 mm
	Shaft shoulder or fit length	21.5 mm, +0/-0.13 mm
	Shaft diameter	Diameter 19 mm, +0/-0.013 mm
	Maximum overall height	93.5 mm maximum
	Front protrusion length	35 mm $\pm$ 1 mm
	Motor body length	106.7 mm $\pm$ 1.5 mm
Mechanical View 3	Mounting hole quantity and diameter	4 holes, diameter 6.5
	Mounting hole angular position	45 degrees
	Square mounting flange size	Square 80
	Mounting bolt circle diameter	Diameter 90 $\pm$ 0.1

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.