

PRODUCT DATASHEET

ES-SM-A01-130D-T14P33NM-3000W-008

AC Servo Motors

AC Servo Motors | ES-SM-A01-130D Standard 130 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 14.33 Nm, instantaneous Maximum Torque 43 Nm and rated Speed 2000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	14.33	Nm
Instantaneous Maximum Torque	43	Nm
Rated Speed	2000	rpm
Continuous Rated Output Power	3000	W
Instantaneous Maximum Current	22.7 ref.)	A
Flange Size	130	mm
Torque Constant	2.56	Nm/A
Rated Voltage	560	V AC
Rated Line Voltage	560	V

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	14.33	Nm
Instantaneous Maximum Torque	43	Nm
Rated Speed	2000	rpm
Continuous Rated Output Power	3000	W
Torque Constant	2.56	Nm/A
Bearing Axial Force	392	N
Bearing Radial Force	980	N
Rated Power	3000	W
ELECTRICAL		
Rated Voltage	560	V AC
Rated Line Voltage	560	V

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ELECTRICAL		
Instantaneous Maximum Current	22.7 ref.)	A
Back EMF Constant	154.8 ref.)	V/krpm
Insulation Class	F	
Motor Outlet Mode	HFO21 + HFO18 aviation connectors	
Pole Pairs	5	
Rated Current	7 ref.)	A
Maximum Allowed Voltage Slew Rate	13	KV/ μ s
Rotational Back-EMF Constant	154.8 ref.)	V/krpm
Electrical Time Constant	13.75	ms
Position Feedback Device	23-bit multi-turn communication optical absolute encoder	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Flange Size	130	mm	
Inertia Level	Medium inertia		
Holding Brake Available	With holding brake		
Mechanical Time Constant	1.08 / 1.06	ms	Brake Configuration: without_brake
Rotor Inertia	31 kgcm ² / 30 Kg·cm ²		Brake Configuration: without_brake
Bearing Radial Force Capacity	980	N	
Bearing Axial Force Capacity	392	N	
ENVIRONMENTAL			
Altitude and Derating Rule	Maximum altitude 4000 m; above 1000 m, power derates 1.5% per 100 m		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Key length	40 mm
	Key width	6 mm
	Key depth	5 mm
	Shaft length with tolerance	24.5 0/-0.2 mm
	Mounting flange diameter with tolerance	Ø110 0/-0.035 mm
	Shaft diameter with tolerance	Ø22 0/-0.013 mm
	Mounting face to shaft end distance (reference)	5.5 mm (reference)
	Front protrusion length (reference)	13.5 mm (reference)
	Motor body length	55±1 mm
	Overall length	273.5±1.5 mm
Mechanical View 3	Mounting bolt circle diameter	Ø145±0.2
	Mounting hole quantity and diameter	4× Ø9
	Mounting hole angular position 1	45°
	Mounting hole angular position 2	
	Flange face dimension	130×130 square

[View Product Online](#)
[Request Engineering Data](#)
[Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.