

PRODUCT DATASHEET

ES-SM-A01-130D-T7P16NM-1500W-012

AC Servo Motors


AC Servo Motors | ES-SM-A01-130D Standard 130 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 7.16 N·m, instantaneous Maximum Torque 21.5 N·m and rated Speed 2000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	7.16	N·m
Instantaneous Maximum Torque	21.5	N·m
Rated Speed	2000	rpm
Continuous Rated Output Power	1500	W
Instantaneous Maximum Current	25 ref.)	A
Flange Size	130	mm
Torque Constant	1.1	N·m/A
Rated Voltage	320	V AC
Rated Line Voltage	320	V



Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	7.16	Nm
Instantaneous Maximum Torque	21.5	Nm
Rated Speed	2000	rpm
Continuous Rated Output Power	1500	W
Torque Constant	1.1	Nm/A
Bearing Axial Force	392	N
Bearing Radial Force	980	N
Rated Power	1500	W
ELECTRICAL		
Rated Voltage	320	V AC
Rated Line Voltage	320	V
Instantaneous Maximum Current	25 ref.)	A
Back EMF Constant	66.9 ref.)	V/krpm
Insulation Class	F	
Motor Outlet Mode	HFO21 + HFO18 aviation connectors	
Pole Pairs	5	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
ELECTRICAL			
Rated Current	7.7 ref.)	A	
Maximum Allowed Voltage Slew Rate	8	KV/ μ s	
Rotational Back-EMF Constant	66.9 ref.)	V/krpm	
Electrical Time Constant	10.95	ms	
Position Feedback Device	Single-turn communication optical encoder		
MECHANICAL			
Flange Size	130	mm	
Inertia Level	Medium inertia		
Holding Brake Available	With holding brake		
Mechanical Time Constant	1.48 / 1.42	ms	Brake Configuration: without_brake
Rotor Inertia	16.95 kgcm ² / 15.95 Kg·cm ²		Brake Configuration: without_brake
Bearing Radial Force Capacity	980	N	
Bearing Axial Force Capacity	392	N	
ENVIRONMENTAL			
Altitude and Derating Rule	Maximum altitude 4000 m; above 1000 m, power derates 1.5% per 100 m		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Key length	Key length 40
	Key width	Key width 6
	Component label	KEY label
Mechanical View 3	Mounting hole pitch circle diameter	Diameter 145 ±0.2
	Mounting hole quantity and diameter	4 holes, diameter 9
	Mounting hole angular layout	45 degree angular offsets on mounting pattern
	Square flange outside size	130

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 4	Leader label 1	Label 1
	Leader label 2	Label 2
	Keyway identification	KEY
	Keyway related height dimension	24.5 with tolerance +0/-0.2
	Key width	5
	Shaft diameter	Diameter 22 with tolerance +0/-0.013
	Outer envelope diameter	Diameter 110 with tolerance +0/-0.035
	Shaft end thread or hole callout	CM6L18
	End shoulder width	5
	Reference axial distance	13.5 reference
	Shaft projection length	55 ±1
	Motor body length	223.5 ±1.5

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.