

PRODUCT DATASHEET

ES-SM-A02-060S-TOP64NM-200W-001

AC Servo Motors


AC Servo Motors | ES-SM-A02-060S High-Response 60 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 0.64 Nm, instantaneous Maximum Torque 1.92 Nm and rated Speed 3000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	0.64	N·m
Instantaneous Maximum Torque	1.92	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	200	W
Instantaneous Maximum Current	4.8	A
Flange Size	60	mm
Torque Constant	0.48	N·m/A
Rated Voltage	220	V AC
Rated Line Voltage	220	V



Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	0.64	Nm
Instantaneous Maximum Torque	1.92	Nm
Rated Speed	3000	rpm
Continuous Rated Output Power	200	W
Rated Power	200	W
Torque Constant	0.48	Nm/A
ELECTRICAL		
Rated Voltage	220	V AC
Rated Line Voltage	220	V
Instantaneous Maximum Current	4.8	A
Position Feedback Device	2500 PPR incremental encoder	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ELECTRICAL		
Insulation Class	F	
Maximum Allowed Voltage Slew Rate	8	KV/ μ s
Pole Pairs	3	
Rated Current	1.6	A
Rotational Back-EMF Constant	29	V/krpm
Electrical Time Constant	2.03	ms
Motor Outlet Mode	Three-row 15-pin connector	
MECHANICAL		
Flange Size	60	mm
Inertia Level	Low inertia	
Holding Brake Available	Without holding brake	

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Mechanical Time Constant	2.26	ms	
Rotor Inertia	0.375 kg·cm ² / 0.375 Kg·cm ²		Brake Configuration: without_brake
Bearing Radial Force Capacity	180	N	
Bearing Axial Force Capacity	90	N	
ENVIRONMENTAL			
Altitude and Derating Rule	Maximum altitude 4000 m; above 1000 m, power derates 1.5% per 100 m		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		
Operating Temperature	-20 to 40°C (no freezing)		
Protection Rating	IP65, shaft end IP54		
CONFIGURATION			
Output Shaft Type	Keyed shaft		

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	60	mm
Inertia Level	Low inertia	
Holding Brake Available	Without holding brake	
Mechanical Time Constant	2.26	ms
Rotor Inertia	0.375 kgcm ² / 0.375 Kg·cm ²	
Bearing Radial Force Capacity	180	N


Dimensional Drawings




Mechanical View 1



Power Connector Pinout



Mechanical View 3



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Mounting hole diameter and quantity	4 holes, $\phi 5.5$ mm each
	Mounting hole angular distribution	45° angular spacing
	Mounting hole pitch circle diameter	$\phi 70 \pm 0.1$ mm
	Square housing side length	60 mm $\times$ 60 mm square
Mechanical View 3	Keyway width	16 mm
	Keyway height/depth	5 mm
	Shaft diameter	$\phi 50$ 0/-0.016 mm
	Shaft length	16 -0.13 mm
	Shaft end diameter	$\phi 14$ -0.011 mm
	Mounting step depth	3 mm
	Mounting boss width	6 mm
	Short section length	30 $\pm$ 1 mm
	Total length	120 $\pm$ 1.5 mm
	Outer diameter	72 mm

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.