

PRODUCT DATASHEET

ES-SM-A02-110D-T5NM-1050W-001

AC Servo Motors


AC Servo Motors | ES-SM-A02-110D High-Response 110 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 5 Nm, instantaneous Maximum Torque 15 Nm and rated Speed 2000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	5	N·m
Instantaneous Maximum Torque	15	N·m
Rated Speed	2000	rpm
Continuous Rated Output Power	1050	W
Instantaneous Maximum Current	17.4	A
Flange Size	110	mm
Torque Constant	0.91	N·m/A
Rated Voltage	220	V AC
Rated Line Voltage	220	V



Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	5	Nm
Instantaneous Maximum Torque	15	Nm
Rated Speed	2000	rpm
Continuous Rated Output Power	1050	W
Torque Constant	0.91	Nm/A
Rated Power	1050	W
ELECTRICAL		
Rated Voltage	220	V AC
Rated Line Voltage	220	V
Instantaneous Maximum Current	17.4	A
Back EMF Constant	55	V/krpm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ELECTRICAL		
Position Feedback Device	2500 PPR incremental encoder	
Insulation Class	F	
Maximum Allowed Voltage Slew Rate	8	KV/ μ s
Motor Outlet Mode	YL-series aviation connector	
Pole Pairs	4	
Rated Current	5.8	A
Rotational Back-EMF Constant	55	V/krpm
Electrical Time Constant	7.5	ms
MECHANICAL		
Flange Size	110	mm
Inertia Level	Medium inertia	

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Holding Brake Available	Without holding brake		
Mechanical Time Constant	1.57	ms	
Rotor Inertia	7.2 kg·cm ² / 7.2 Kg·cm2		Brake Configuration: without_brake
Bearing Radial Force Capacity	630	N	
Bearing Axial Force Capacity	315	N	
ENVIRONMENTAL			
Altitude and Derating Rule	Maximum altitude 4000 m; above 1000 m, power derates 1.5% per 100 m		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		
Operating Temperature	-20 to 40°C (no freezing)		
Protection Rating	IP65, shaft end IP54		

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	110	mm
Inertia Level	Medium inertia	
Holding Brake Available	Without holding brake	
Mechanical Time Constant	1.57	ms
Rotor Inertia	7.2 kgcm ² / 7.2 Kg·cm ²	
Bearing Radial Force Capacity	630	N


Dimensional Drawings




Mechanical View 1



Power Connector Pinout



Mechanical View 3



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Mounting flange bolt hole circle diameter	$\phi 130 \pm 0.1$
	Mounting hole angular position	45°
	Number and diameter of mounting holes	4- $\phi 9$
	Mounting flange envelope dimension	$\square 110$
	Product model identifier	YL2207ZJ-D
		YL2217ZJ
Mechanical View 3	Shaft length	32 mm
	Shaft diameter	$\phi 19.0 / -0.013$ mm
	Keyway width	6 mm
	Keyway depth	
	Key model	CM6L25
	Flange diameter	$\phi 95.0 / -0.035$ mm
	Motor shaft to mounting face distance	41 $\pm$ 1 mm
	Overall length	185 $\pm$ 1 mm
	Maximum height	180 mm (MAX)
	Keyway angle dimension	3 mm
	Lower dimension	
	Bottom spacing	11 mm

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.