PRODUCT DATASHEET

ES-SM-A02-110D-T6NM-1260W-001

AC Servo Motors

AC Servo Motors | ES-SM-A02-110D High-Response 110 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 6 N·m, instantaneous Maximum Torque 18 N·m and rated Speed 2000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	6	N·m
Instantaneous Maximum Torque	18	N·m
Rated Speed	2000	rpm
Continuous Rated Output Power	1260	W
Instantaneous Maximum Current	18.45	A
Flange Size	110	mm
Torque Constant	1.058	N·m/A
Rated Voltage	220	V AC
Rated Line Voltage	220	V



Torque-Speed Curve

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	6	N·m
Instantaneous Maximum Torque	18	N·m
Rated Speed	2000	rpm
Continuous Rated Output Power	1260	W
Torque Constant	1.058	N·m/A
Rated Power	1260	W
ELECTRICAL		
Rated Voltage	220	V AC
Rated Line Voltage	220	V
Instantaneous Maximum Current	18.45	A
Back EMF Constant	64	V/krpm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
ELECTRICAL		
Position Feedback Device	2500 PPR incremental encoder	
Insulation Class	F	
Maximum Allowed Voltage Slew Rate	8	KV/μs
Motor Outlet Mode	YL-series aviation connector	
Pole Pairs	4	
Rated Current	6.15	A
Rotational Back-EMF Constant	64	V/krpm
Electrical Time Constant	7.64	ms
MECHANICAL		
Flange Size	110	mm
Inertia Level	Medium inertia	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Holding Brake Available	Without holding brake		
Mechanical Time Constant	1.66	ms	
Rotor Inertia	8.5 kg·cm² / 8.5 Kg·cm2		Brake Configuration: without_brake
Bearing Radial Force Capacity	630	N	
Bearing Axial Force Capacity	315	N	
ENVIRONMENTAL			
Altitude and Derating Rule	Maximum altitude 4000 m; above 1000 m, power derates 1.5% per 100 m		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		
Operating Temperature	-20 to 40°C (no freezing)		
Protection Rating	IP65, shaft end IP54		

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	110	mm
Inertia Level	Medium inertia	
Holding Brake Available	Without holding brake	
Mechanical Time Constant	1.66	ms
Rotor Inertia	8.5 kg·cm² / 8.5 Kg·cm2	
Bearing Radial Force Capacity	630	N

Dimensional Drawings



Mechanical View 1



Power Connector Pinout



Mechanical View 3



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Mounting flange bolt circle diameter	Φ130±0.1
	Upper-left mounting hole angular position	45°
	Lower-left mounting hole angular position	
	Mounting hole quantity and diameter	4 holes × Φ9
	Motor flange square envelope dimension	110
Mechanical View 3	Shaft length	32 mm
	Keyway width	6 mm
	Keyway depth	9 mm
	Maximum height	180 mm (MAX)
	Keyway identifier	KEY
	Keyway length	3 mm
	Key model reference	CM6L25
	Shaft diameter at mounting end	Φ95 0/-0.035 mm
	Shaft diameter at output end	Φ19 0/-0.013 mm
	Bottom mounting edge distance	3 mm
	Bottom mounting hole spacing	11 mm
	End mounting reference distance	41±1 mm
	Total length	202±1 mm

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.