

PRODUCT DATASHEET

ES-SM-A03-060D-TOP64NM-200W-001

AC Servo Motors


AC Servo Motors | ES-SM-A03-060D Compact 60 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 0.64 N·m, instantaneous Maximum Torque 2.26 N·m and rated Speed 3000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	0.64	N·m
Instantaneous Maximum Torque	2.26	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	200	W
Rated Voltage	220	V AC
Instantaneous Maximum Current	5	A
Flange Size	60	mm
Torque Constant	0.56	N·m/A
Altitude and Derating Rule	highest altitude2000m(1000mfor each increase above100m,Power drop1.5%)	



Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	0.64	Nm
Instantaneous Maximum Torque	2.26	Nm
Rated Speed	3000	rpm
Continuous Rated Output Power	200	W
Torque Constant	0.56	Nm/A
Rated Power	200	W
ELECTRICAL		
Rated Voltage	220	V AC
Instantaneous Maximum Current	5	A
Back EMF Constant	34	V/krpm
Insulation Class	F	
Motor Outlet Mode	Standard socket	
Pole Pairs	5	
Rated Current	1.3	A
Rotational Back-EMF Constant	34	V/krpm
Electrical Time Constant	1.77	ms

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
ELECTRICAL			
Position Feedback Device	17-bit multi-turn communication magnetic absolute encoder		
MECHANICAL			
Flange Size	60	mm	
Inertia Level	Medium inertia		
Holding Brake Available	Without holding brake		
Mechanical Time Constant	1.32	ms	Brake Configuration: without_brake
Rotor Inertia	0.28 / 0.26	Kg-cm ²	Brake Configuration: without_brake
Bearing Radial Force Capacity	245	N	
Bearing Axial Force Capacity	74	N	
ENVIRONMENTAL			
Altitude and Derating Rule	highest altitude 2000m (1000m for each increase above 100m, Power drop 1.5%)		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		
Operating Temperature	-20 to 40°C (no freezing)		
Protection Rating	IP65, shaft end IP54 (Note: with shaft-end oil seal IP54, without oil seal IP50)		
CONFIGURATION			
Output Shaft Type	Keyed shaft		
ADDITIONAL SPECIFICATIONS			
Holding Brake	false		

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	60	mm
Inertia Level	Medium inertia	
Holding Brake Available	Without holding brake	
Mechanical Time Constant	1.32	ms
Rotor Inertia	0.28 / 0.26	Kg·cm ²
Bearing Radial Force Capacity	245	N


Dimensional Drawings




Mechanical View 1



Power Connector Pinout



Mechanical View 3



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Mounting hole position	16 mm
	Mounting hole vertical position	5 mm
	Through hole specification	M3 through hole
	Keyway identifier	Keyway feature
	Position tolerance	Position tolerance $\varnothing 0.04$ relative to datum A
	Perpendicularity tolerance	Perpendicularity 0.04 relative to datum A
	Shaft diameter with tolerance	$\varnothing 14$ h6 (0/-0.011)
	Runout tolerance	Runout 0.02 relative to datum A
	Outer diameter with tolerance	$\varnothing 50$ h7 (0/-0.025)
	Keyway width with tolerance	16 h9 (0/-0.13)
	Bolt specification	M5×15 bolt
	Datum A	
	Assembly note	Install key and oil seal
	Keyway depth	3 ± 0.3 mm
	Axial length	30 ± 1 mm
	Overall axial length	74 ± 1 mm
	Reference dimension	76 mm (reference)
	Local height	6 mm

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 3	Flange outer diameter	Ø70±0.1
	Flange mounting holes	4×Ø5.5
	Flange square envelope dimension	60×60 square

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.