

PRODUCT DATASHEET

ES-SM-A03-060S-TOP64NM-200W-002

AC Servo Motors

AC Servo Motors | ES-SM-A03-060S Compact 60 mm AC Servo Motor Series

Product Overview

AC Servo Motors with rated Torque 0.64 Nm, instantaneous Maximum Torque 1.92 Nm and rated Speed 3000 rpm.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	0.64	N·m
Instantaneous Maximum Torque	1.92	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	200	W
Rated Voltage	220	V AC
Instantaneous Maximum Current	5	A
Flange Size	60	mm
Torque Constant	0.5	Nm/A
Altitude and Derating Rule	highest altitude2000m,1000mabove,every rise100m,Power drop1.5%	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	0.64	Nm
Instantaneous Maximum Torque	1.92	Nm
Rated Speed	3000	rpm
Continuous Rated Output Power	200	W
Torque Constant	0.5	Nm/A
Rated Power	200	W
ELECTRICAL		
Rated Voltage	220	V AC
Instantaneous Maximum Current	5	A
Back EMF Constant	30	V/krpm
Insulation Class	F	
Motor Outlet Mode	Standard socket	
Pole Pairs	5	
Rated Current	1.55	A
Rotational Back-EMF Constant	30	V/krpm
Electrical Time Constant	1.9	ms

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
ELECTRICAL			
Position Feedback Device	17-bit multi-turn communication magnetic absolute encoder		
MECHANICAL			
Flange Size	60	mm	
Inertia Level	Low inertia		
Holding Brake Available	With holding brake		
Mechanical Time Constant	1.31 / 1.28	ms	Brake Configuration: without_brake
Rotor Inertia	0.174 / 0.17	Kg-cm ²	Brake Configuration: without_brake
Bearing Radial Force Capacity	180	N	
Bearing Axial Force Capacity	90	N	
ENVIRONMENTAL			
Altitude and Derating Rule	highest altitude 2000m, 1000m above, every rise 100m, Power drop 1.5%		
Operating Environment	Keep away from corrosive or flammable gases, oil droplets and dust		
Operating Humidity	≤90% RH, non-condensing		
Operating Temperature	-20 to 40°C (no freezing)		
Protection Rating	IP67, shaft end IP54 (Note: with shaft-end oil seal IP54, without oil seal IP50)		
CONFIGURATION			
Output Shaft Type	Keyed shaft		
ADDITIONAL SPECIFICATIONS			
Holding Brake	1		

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	60	mm
Inertia Level	Low inertia	
Holding Brake Available	With holding brake	
Mechanical Time Constant	1.31 / 1.28	ms
Rotor Inertia	0.174 / 0.17	Kg·cm ²
Bearing Radial Force Capacity	180	N


Dimensional Drawings




Mechanical View 1




Power Connector Pinout



Mechanical View 3



Mechanical View 4



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Mounting hole pitch circle diameter	Pitch circle diameter $\varnothing 70 \pm 0.1$
	Mounting hole quantity and diameter	4 holes, diameter $\varnothing 5.5$
	Square mounting flange side length	Square flange 60×60
Mechanical View 3	Left geometric tolerance callout	Geometric tolerance $\varnothing 0.04$ relative to datum A
	Upper geometric tolerance callout	Geometric tolerance 0.04 relative to datum A; characteristic symbol not captured by OCR source
	Shaft diameter	Diameter 14 mm, upper deviation 0, lower deviation -0.011
	Shaft end geometric tolerance	Geometric tolerance 0.035 relative to datum A
	Mounting pilot diameter	Diameter 50 mm, upper deviation 0, lower deviation -0.025
	Shaft extension diameter or step size	Size 16 mm, upper deviation 0, lower deviation -0.13
	Threaded hole specification	M5 thread, depth or length 15
	Datum A	
	Short axial offset	3
	Axial step distance	6
	Shaft extension length	30 ± 1
	Body length	109.1 ± 1.5
	Overall height	79

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 4	Key length	Key length 16 mm
	Key width	Key width 5 mm
	Key height	Key height 5 mm
	Key label	Key component/detail label

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.