PRODUCT DATASHEET

ES-SM-L01-040S-V48-T0P32NM-100W-004

Low-Voltage Servo Motors

Low-Voltage Servo Motors | ES-SM-L01-040S 48V 40 mm Low-Voltage Servo Motor Series


Product Overview

Low-Voltage Servo Motors with rated Torque 0.32 N·m, rated Speed 3000 rpm and continuous Rated Output Power 100 W.

Configuration Context	Feedback device: Multi-turn communication magnetic absolute encoder

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	0.32	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	100	W
Rated Voltage	48	VDC
Rated Line Voltage	48	V
Continuous Rated Current	3.2	A
Instantaneous Maximum Current	11.5	A
Flange Size	40	mm
Allowable Axial Force	60	N



Torque-Speed Curve

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	0.32	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	100	W
ELECTRICAL		
Rated Voltage	48	VDC
Rated Line Voltage	48	V
Continuous Rated Current	3.2	A
Instantaneous Maximum Current	11.5	A
Pole Pairs	5	
Rotational Back-EMF Constant	7	V/krpm
Electrical Time Constant	1.27	ms
Insulation Class	F	
Motor Outlet Mode	Communication encoder connector	
MECHANICAL		
Flange Size	40	mm

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Inertia Level	Low inertia		
Allowable Radial Force	120	N	
Mechanical Time Constant	0.67	ms	Brake Configuration: with_brake / Brake Configuration: without_brake
Rotor Inertia	0.033	Kg·cm 2	Brake Configuration: without_brake / Brake Configuration: with_brake
Allowable Axial Force	60	N	
INTEGRATION			
Feedback Device	Multi-turn communication magnetic absolute encoder		
ENVIRONMENTAL			
Operating Environment	Free from corrosive or flammable gases, oil droplets, and dust		
Operating Humidity	≤90% RH, non-condensing	%RH	
Altitude and Derating Rule	Maximum 2,000 m; derate power 1.5% per 100 m above 1,000	m	
Operating Temperature	-20 to 40	°C	
Protection Grade	Body IP65; shaft end IP54 without oil seal, IP65 with oil seal		
CONFIGURATION			
Output Shaft Type	Keyed shaft		
ADDITIONAL SPECIFICATIONS			
Cooling Method	Fully enclosed, self-cooled		

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	40	mm
Inertia Level	Low inertia	
Allowable Radial Force	120	N
Mechanical Time Constant	0.67	ms
Rotor Inertia	0.033	Kg·cm2
Allowable Axial Force	60	N


Dimensional Drawings




Mechanical View 1



Power Connector Pinout



Mechanical View 3



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Maximum protrusion height	15 max
	Mounting hole quantity and diameter	2 holes, diameter 3.5
	Mounting hole angular position	45 degrees
	Square flange envelope size	Square 40
	Pilot diameter	Diameter 45 ±0.2
Mechanical View 3	Section view identifier	Section A-A
	Keyway slot width	3 mm, +0 / -0.014
	Shaft end sectional height or envelope dimension	9.2 mm
	Shaft end length	12 mm
	Threaded hole size and depth	M3 thread, depth 8 mm
	Shaft diameter tolerance	Diameter 8 mm, +0 / -0.013
	Shaft end reference length	20.5 mm ±0.2
	Step offset length	2.8 mm
	End step width	5 mm
	Main body length	126.2 mm ±1
	Shaft end total projection length	23.8 mm ±0.8

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.