PRODUCT DATASHEET

ES-SM-L02-080D-V48-T2P39NM-750W-003

Low-Voltage Servo Motors

Low-Voltage Servo Motors | ES-SM-L02-080D Compact 80 mm Low-Voltage Servo Motor Series


Product Overview

Low-Voltage Servo Motors with rated Torque 2.39 N·m, rated Speed 3000 rpm and continuous Rated Output Power 750 W.

Configuration Context	Feedback device: Multi-turn communication magnetic absolute encoder

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	2.39	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	750	W
Rated Voltage	48	VDC
Rated Line Voltage	48	V
Continuous Rated Current	18.1	A
Instantaneous Maximum Current	56	A
Flange Size	80	mm
Allowable Axial Force	90	N



Torque-Speed Curve

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	2.39	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	750	W
ELECTRICAL		
Rated Voltage	48	VDC
Rated Line Voltage	48	V
Continuous Rated Current	18.1	A
Instantaneous Maximum Current	56	A
Pole Pairs	5	
Rotational Back-EMF Constant	8.9	V/krpm
Electrical Time Constant	2.84	ms
Insulation Class	F	
Motor Outlet Mode	Dedicated motor socket	
MECHANICAL		
Flange Size	80	mm
Inertia Level	Medium inertia	

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Allowable Radial Force	270	N	
Mechanical Time Constant	1.02 / 1.14	ms	Brake Configuration: without_brake / Brake Configuration: with_brake
Rotor Inertia	1.45	Kg·cm 2	Brake Configuration: without_brake / Brake Configuration: with_brake
Allowable Axial Force	90	N	
INTEGRATION			
Feedback Device	Multi-turn communication magnetic absolute encoder		
ENVIRONMENTAL			
Operating Environment	Free from corrosive or flammable gases, oil droplets, and dust		
Operating Humidity	≤90% RH, non-condensing	%RH	
Altitude and Derating Rule	Maximum 2,000 m; derate power 1.5% per 100 m above 1,000	m	
Operating Temperature	-5 to 40	°C	
Protection Grade	IP65		
CONFIGURATION			
Output Shaft Type	Keyed shaft		
Motor Version	Ultra-short version		
ADDITIONAL SPECIFICATIONS			
Cooling Method	Fully enclosed, self-cooled		

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	80	mm
Inertia Level	Medium inertia	
Allowable Radial Force	270	N
Mechanical Time Constant	1.02 / 1.14	ms
Rotor Inertia	1.45	Kg·cm2
Allowable Axial Force	90	N


Dimensional Drawings




Mechanical View 1




Power Connector Pinout



Mechanical View 3



Mechanical View 4



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Key length	25 mm
	Key width	6 mm
Mechanical View 3	Main shaft diameter with tolerance	Ø70h7 (-0.03)
	Main shaft position tolerance	Position tolerance ⊕0.04 relative to datum A
	Shaft shoulder diameter with tolerance	Ø21.5 0/-0.2
	Keyway identification	Keyway present
	Mounting threaded hole	M6 thread, depth 15mm
	Mounting hole diameter with tolerance	Ø19h6 (-0.013)
	Mounting hole depth	3±0.3
	Mounting surface perpendicularity	Perpendicularity tolerance 0.06 relative to datum A
	Feature dimension	8
	Axial mounting dimension 1	35±1
	Overall axial length	117.5±0.5
	End face perpendicularity	Perpendicularity tolerance 0.02 relative to datum A
	Datum A	Datum A (main shaft axis)
	Reference dimension	(69.4)

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 4	Mounting face width with tolerance	15.5 -0.1
	Mounting flange bolt circle diameter	Ø90
	Mounting hole quantity and diameter	4-Ø6.5
	Mounting flange envelope dimension	□80

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.