PRODUCT DATASHEET

ES-SM-L02-080D-V96-T2P39NM-750W-001

Low-Voltage Servo Motors

Low-Voltage Servo Motors | ES-SM-L02-080D Compact 80 mm Low-Voltage Servo Motor Series


Product Overview

Low-Voltage Servo Motors with rated Torque 2.39 N·m, rated Speed 3000 rpm and continuous Rated Output Power 750 W.

Configuration Context	Feedback device: Multi-turn communication magnetic absolute encoder

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	2.39	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	750	W
Rated Voltage	96	VDC
Rated Line Voltage	96	V
Continuous Rated Current	9.6	A
Instantaneous Maximum Current	32.5	A
Flange Size	80	mm
Allowable Axial Force	90	N



Torque-Speed Curve

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	2.39	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	750	W
ELECTRICAL		
Rated Voltage	96	VDC
Rated Line Voltage	96	V
Continuous Rated Current	9.6	A
Instantaneous Maximum Current	32.5	A
Pole Pairs	5	
Rotational Back-EMF Constant	17.3	V/krpm
Electrical Time Constant	3.17	ms
Insulation Class	F	
Motor Outlet Mode	Communication encoder connector	
MECHANICAL		
Flange Size	80	mm
Inertia Level	Medium inertia	

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Allowable Radial Force	270	N	
Mechanical Time Constant	0.92	ms	Brake Configuration: without_brake / Brake Configuration: with_brake
Rotor Inertia	1.45	Kg·cm 2	Brake Configuration: with_brake / Brake Configuration: without_brake
Allowable Axial Force	90	N	
INTEGRATION			
Feedback Device	Multi-turn communication magnetic absolute encoder		
ENVIRONMENTAL			
Operating Environment	Free from corrosive or flammable gases, oil droplets, and dust		
Operating Humidity	≤90% RH, non-condensing	%RH	
Altitude and Derating Rule	Maximum 2,000 m; derate power 1.5% per 100 m above 1,000	m	
Operating Temperature	-20 to 40	°C	
Protection Grade	IP54		
CONFIGURATION			
Output Shaft Type	Keyed shaft		
Motor Version	Ultra-short version		
ADDITIONAL SPECIFICATIONS			
Cooling Method	Fully enclosed, self-cooled		

Dimensional & Integration Overview


Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	80	mm
Inertia Level	Medium inertia	
Allowable Radial Force	270	N
Mechanical Time Constant	0.92	ms
Rotor Inertia	1.45	Kg·cm2
Allowable Axial Force	90	N


Dimensional Drawings




Mechanical View 1




Power Connector Pinout



Mechanical View 3



Mechanical View 4



Feedback Connector Pinout

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Mounting Dimension with Tolerance	15.5 +0/-0.1
	Angular Dimension	45°
	Mounting Bolt Circle Diameter	Ø90
	Mounting Hole Quantity and Diameter	4-Ø6.5
	Square Envelope Dimension	□80
Mechanical View 3	Keyway notation	Keyway present
	Mounting thread specification	M6×15
	Shaft journal diameter with tolerance	Ø70h7 (0/-0.03)
	Shaft journal position tolerance relative to datum A	Position tolerance ø0.04 relative to datum A
	Shaft shoulder length with tolerance	21.5 (0/-0.2)
	Maximum envelope dimension	95 max
	Shaft end diameter with tolerance	Ø19h6 (0/-0.013)
	Shaft extension length	8
	Keyway depth with tolerance	3±0.3
	Keyway perpendicularity tolerance relative to datum A	Perpendicularity tolerance 0.06 relative to datum A
	Axial mounting dimension 1	35±1
	Overall length dimension	80.8±0.5
	End face parallelism tolerance relative to datum A	Parallelism tolerance 0.02 relative to datum A

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 4	Keyway length	25 mm
	Keyway width	6 mm
	Key height/depth	

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.