PRODUCT DATASHEET

ES-SM-L02-080S-V48-T3P18NM-1000W-003

Low-Voltage Servo Motors

Low-Voltage Servo Motors | ES-SM-L02-080S Compact 48V 80 mm Low-Voltage Servo Motor Series

Product Overview

Low-Voltage Servo Motors with rated Torque 3.18 N·m, rated Speed 3000 rpm and continuous Rated Output Power 1000 W.

Key Specifications

PARAMETER	VALUE	UNIT
Rated Torque	3.18	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	1000	W
Rated Voltage	48	VDC
Rated Line Voltage	48	V
Continuous Rated Current	25.8	A
Instantaneous Maximum Current	81	A
Flange Size	80	mm
Allowable Axial Force	147	N

Technical Specifications

PARAMETER	SPECIFICATION	UNIT
PERFORMANCE		
Rated Torque	3.18	N·m
Rated Speed	3000	rpm
Continuous Rated Output Power	1000	W
ELECTRICAL		
Rated Voltage	48	VDC
Rated Line Voltage	48	V
Continuous Rated Current	25.8	A
Instantaneous Maximum Current	81	A
Pole Pairs	5	
Rotational Back-EMF Constant	8.23	V/krpm
Electrical Time Constant	3.79	ms
Insulation Class	F	
Motor Outlet Mode	Dedicated motor socket	
MECHANICAL		
Flange Size	80	mm

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
MECHANICAL			
Inertia Level	Low inertia		
Allowable Radial Force	392	N	
Mechanical Time Constant	0.63	ms	Brake Configuration: with_brake / Brake Configuration: without_brake
Rotor Inertia	1.16	Kg·cm 2	Brake Configuration: with_brake / Brake Configuration: without_brake
Allowable Axial Force	147	N	
ENVIRONMENTAL			
Operating Environment	Free from corrosive or flammable gases, oil droplets, and dust		
Operating Humidity	≤90% RH, non-condensing	%RH	
Altitude and Derating Rule	Maximum 2,000 m; derate power 1.5% per 100 m above 1,000	m	
Operating Temperature	-20 to 40	°C	
Protection Grade	IP65		
CONFIGURATION			
Output Shaft Type	Keyed shaft		
ADDITIONAL SPECIFICATIONS			
Cooling Method	Fully enclosed, self-cooled		

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Flange Size	80	mm
Inertia Level	Low inertia	
Allowable Radial Force	392	N
Mechanical Time Constant	0.63	ms
Rotor Inertia	1.16	Kg•cm2
Allowable Axial Force	147	N

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.