

PRODUCT DATASHEET

ES-ST-11H2052-100-4AL

Hybrid Stepper Motors

Hybrid Stepper Motors | 28 mm Hybrid Stepper Motor Series - ES-ST-HY03

Product Overview

Hybrid Stepper Motors with holding Torque 0.14 N·m, continuous Rated Current 1 A and step Angle 1.8 °.

Key Specifications

PARAMETER	VALUE	UNIT
Holding Torque	0.14	N·m
Continuous Rated Current	1	A
Step Angle	1.8	°
Body Length	52	mm
Weight	0.28	kg
Temperature Rise	80	°C
Number of Phases	2	
Phase Resistance	4.7 ±10%	Ω
Insulation Class	B	

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Holding Torque	0.14	Nm	
ELECTRICAL			
Continuous Rated Current	1	A	
Step Angle	1.8	°	
Temperature Rise	80	°C	
Number of Phases	2		
Phase Resistance	4.7 ±10%	Ω	Measurement: 20 °C
Phase Inductance	4.6 ±20%	mH	Measurement: 1V, 1kHz
Insulation Class	B		
Insulation Resistance	100 (500 VDC)	MΩ	
MECHANICAL			
Body Length	52	mm	
Weight	0.28	kg	

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Body Length	52	mm
Weight	0.28	kg

Dimensional Drawings



2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Motor body length	52 mm
	Shaft extension length	20 ± 1 mm
	Shaft step length	15 ± 0.2 mm
	Front shoulder thickness	1.5 mm
	Shaft flat height	4.5 ± 0.1 mm
	Shaft diameter with tolerance	Diameter 5 mm, upper deviation +0 mm, lower deviation -0.013 mm
Mechanical View 3	Motor front face square envelope	Square 28
	Mounting hole center spacing	Square bolt pattern 23 ± 0.2
	Central diameter with unilateral tolerance	Diameter 22, upper deviation -0, lower deviation -0.05
	Mounting threaded hole quantity and thread size	4 × M2.5 threaded holes
	Minimum thread depth	Minimum depth 2.5

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.