

PRODUCT DATASHEET

ES-ST-11HS2033-4D-100

Hollow Shaft Stepper Motors

Hollow Shaft Stepper Motors | 28 mm Hollow-Shaft Stepper Motor Series - ES-ST-HS03

Product Overview

Hollow Shaft Stepper Motors with continuous Rated Current 1 A RMS, step Angle 1.8 ° and body Length 33 mm.

Key Specifications

PARAMETER	VALUE	UNIT
Continuous Rated Current	1	A RMS
Step Angle	1.8	°
Body Length	33	mm
Motor Construction Type	Hollow Shaft Stepper Motor	
Frame Size	28	mm
Lead Wire Configuration	Bipolar, 4 flying leads	
Lead Wire Count	4	
NEMA Size	11	
Phase Count	2	

Technical Specifications


PARAMETER	SPECIFICATION	UNIT	NOTES
ELECTRICAL			
Continuous Rated Current	1	A RMS	Measurement Basis: rms
Step Angle	1.8	°	
Lead Wire Configuration	Bipolar, 4 flying leads		
Lead Wire Count	4		
Phase Count	2		
MECHANICAL			
Body Length	33	mm	
Frame Size	28	mm	
Shaft Configuration	Double shaft		
NEMA Size	11		
CONFIGURATION			
Motor Construction Type	Hollow Shaft Stepper Motor		

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Body Length	33	mm
Frame Size	28	mm
Shaft Configuration	Double shaft	
NEMA Size	11	

Dimensional Drawings



2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Square housing outer dimension	28mm square
	Mounting face dimension	23±0.2mm square
	Output shaft diameter	Φ22 +0/-0.05
	Through hole diameter	Φ5 +0.2/-0 through hole
	Mounting threaded hole specification	4× M2.5 threaded holes
	Minimum thread depth	2.5mm minimum
Mechanical View 3	Left end face width	10±1 mm
	Motor body length	33.35±0.5 mm
	Right end face width	10±1 mm
	Mounting face depth or boss height	1.5 mm
	Left output shaft diameter	Φ7 +0/-0.013 mm
	Right output shaft diameter	
	Datum D (left side)	Datum D
	Datum D (right side)	

[View Product Online](#) [Request Engineering Data](#) [Request a Quote](#)

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.