PRODUCT DATASHEET

ES-ST-23H2065-300-4AL

Hybrid Stepper Motors

Hybrid Stepper Motors | 57 mm Hybrid Stepper Motor Series - ES-ST-HY06

Product Overview

Hybrid Stepper Motors with holding Torque 1.6 N·m, continuous Rated Current 3 A and step Angle 1.8 °.

Key Specifications

PARAMETER	VALUE	UNIT
Holding Torque	1.6	N·m
Continuous Rated Current	3	A
Step Angle	1.8	°
Body Length	65	mm
Weight	0.86	kg
Temperature Rise	80	°C
Number of Phases	2	
Phase Resistance	0.9 ±10%	Ω
Insulation Class	B	

Technical Specifications

PARAMETER	SPECIFICATION	UNIT	NOTES
PERFORMANCE			
Holding Torque	1.6	N·m	
ELECTRICAL			
Continuous Rated Current	3	A	
Step Angle	1.8	°	
Temperature Rise	80	°C	
Number of Phases	2		
Phase Resistance	0.9 ±10%	Ω	Measurement: 20 °C
Phase Inductance	2.7 ±20%	mH	Measurement: 1 V, 1 kHz
Insulation Class	B		
Insulation Resistance	100 (500 VDC)	MΩ	
MECHANICAL			
Body Length	65	mm	
Weight	0.86	kg	

Dimensional & Integration Overview

Mechanical Overview

PARAMETER	VALUE	UNIT
Body Length	65	mm
Weight	0.86	kg

Dimensional Drawings



Mechanical View 1



Power Connector Pinout



Mechanical View 3

2D Drawing Dimensions & Callouts

VIEW	FIELD	VALUE
Mechanical View 1	Envelope width	57.15 mm square
	Mounting flange dimension	47.14 ±0.25 mm square
	Shaft diameter	φ38.1 +0/-0.05 mm
	Mounting holes (4 places)	4× φ5 +0.3/-0 mm
Mechanical View 3	Mounting flange width	20.6±1 mm
	Overall length	65.5 mm
	Boss depth	1.6 mm
	Mounting flange length	15±0.2 mm
	Mounting flange height	7.5±0.1 mm
	Shaft diameter	Ø8 +0/-0.013 mm

View Product Online Request Engineering Data Request a Quote

01 Specifications are subject to change without notice. Verify the current product configuration before final design release.

02 2D drawings, CAD files and integration documentation are controlled documents and are supplied separately on request.