

ENGINEERING DOCUMENTATION

Slotted Brushless DC Motor

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-DC-SL05-M001	DRAFT-08 / 28 Aug 2026	Engineering Integration Reference

Integration Overview


Compact electric motor for specified rotary actuation. This guide supports mounting, shaft, load-path, drive, thermal, cable and commissioning planning for ES-DC-SL05-M001.

Key Integration Facts

INTEGRATION ITEM	VALUE
Rated Torque	0.2 Nm
Rated Speed	10000 rpm
Torque Constant	0.036 Nm/A
Continuous Rated Output Power	209.4 W
Instantaneous Maximum Torque	0.6 Nm
No-Load Rotational Speed	12000 rpm
Pole Pairs	2
Instantaneous Maximum Current	16.5 A

3D Orientation Reference

This axonometric reference provides a quick orientation check for the motor or actuator body, output interface and mounting relationship of ES-DC-SL05-M001.



Axonometric Orientation View


Orientation reference only. Use the exact-SKU parameter table and mechanical drawing for dimensions, hole geometry, fits and machining decisions.

Exact-SKU Interface Cross-Reference


INTEGRATION TOPIC	EXACT-SKU REFERENCE
Motor envelope and output orientation	Body Length: 75 mm. Confirm interface geometry, fits and installation details in the exact-SKU mechanical drawing.
Drive and motion boundaries	Rated Voltage: 48 V; Continuous Rated Current: 5.5 A; Rated Torque: 0.2 N·m; Rated Speed: 10000 rpm. Confirm interface geometry, fits and installation details in the exact-SKU mechanical drawing.
Installed load and thermal reference	Rotor Inertia: 0.084 kg·cm ² ; Duty Cycle: S2 . Confirm interface geometry, fits and installation details in the exact-SKU mechanical drawing.

Product Structure & Views


These views present product structure, mounting interfaces and relevant integration geometry for this SKU.



Mechanical View 1



Mechanical View 2



Mechanical View 3

VIEW	FIELD	VALUE
Mechanical View 1	M3 threaded hole	4 × M3 through holes, equally spaced
	Bolt circle diameter	33±0.1
Mechanical View 2	Shaft end diameter with tolerance	5 0/-0.013 mm
	Motor flange outer diameter	42 mm
	Main output shaft diameter with tolerance	25 0/-0.03 mm
	Shaft extension length	15±0.1 mm
	Main shaft protrusion length	10±0.1 mm
	Overall motor length	73 mm
	Total output shaft length	14±1 mm
	Local section hole diameter	4.5 0/-0.1

Technical Specifications

PARAMETER	VALUE	UNIT
Rated Torque	0.2	Nm
Rated Speed	10000	rpm
Torque Constant	0.036	Nm/A
Continuous Rated Output Power	209.4	W
Instantaneous Maximum Torque	0.6	Nm
No-Load Rotational Speed	12000	rpm
Pole Pairs	2	
Instantaneous Maximum Current	16.5	A
Rotational Back-EMF Constant	3.77	V/krpm
Continuous Rated Current	5.5	A
Dielectric strength	500VAC/1KHz/1mA/1s	
Insulation Resistance	100 MOhm 20C	
Position Feedback Device		
No-load Current	0.86	A
Rated Voltage	48	V
Rotor Inertia	0.084	kgcm ²

Technical Specifications - Continued

PARAMETER	VALUE	UNIT
Body Length	75	mm
Frame size	42	
Winding connection		
Housing shape	Round	
Noise	≤50	dB
Commutation angle	120°	°
Housing-to-Ambient Thermal Resistance	0.085	K/W
Motor efficiency	80	%
Line resistance	0.24	Ω
Maximum Winding Temperature	75	°C
Housing Type	Aluminum housing	
Line inductance	0.15	mH
Ambient temperature	25	°C
Duty Cycle	S2	
Motor Weight	425.8	g

Mounting, Shaft and Load Path

- Support the complete mounting face, preserve locating features and verify fastener engagement without distorting the housing.
- Align the shaft and coupling before tightening, and validate radial load, axial load, overhung distance, belt tension, inertia and shock for the installed mechanism.

Drive, Electrical and Motion Integration

- Coordinate supply, drive current limit, speed, torque and fault protection with the actual load and duty cycle.
- Use applicable wiring data for conductor identity, polarity, phase pairing, shielding and grounding; do not infer these from the product view.

Thermal, Cable and Commissioning Conditions

- Validate housing and winding temperature over the intended operating cycle, ambient condition, mounting heat path and enclosure airflow.
- Provide strain relief and service clearance, then commission at reduced energy and verify direction, current limits, motion response, temperature and fault behavior.

Integration Checklist

- | | |
|----|---|
| 01 | Confirm the exact-SKU drawing and parameter set. |
| 02 | Verify mounting geometry, locating features, shaft engagement, coupling alignment and service clearance. |
| 03 | Validate torque, speed, inertia, radial and axial loads, overhung distance and shock. |
| 04 | Set drive, current, motion, wiring, grounding and thermal boundaries from applicable product documentation. |
| 05 | Commission at reduced energy and verify direction, motion response, temperature and fault behavior. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-DC-SL05-M001 and is intended for dimensional evaluation and preliminary integration. It is not a applicable manufacturing drawing, motor or actuator application approval, wiring definition, drive-selection approval, machinery risk assessment, safety validation or production authorization. Before design freeze, installation or energization, verify all dimensions, mounting and locating features, moving envelopes, shaft or output geometry, permissible loads, alignment, supply and current limits, wiring, motion profile, duty cycle, thermal condition, cable routing, environmental boundaries, maintenance and fault response against the applicable EmbodyStack engineering data for this exact SKU. Validate the complete installed system under intended operating and fault conditions.