

ENGINEERING DOCUMENTATION

Slotted Brushless DC Motor

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-DC-SL06-M001	DRAFT-08 / 28 Aug 2026	Engineering Integration Reference

Integration Overview


Compact electric motor for specified rotary actuation. This guide supports mounting, shaft, load-path, drive, thermal, cable and commissioning planning for ES-DC-SL06-M001.

Key Integration Facts


INTEGRATION ITEM	VALUE
Rated Torque	0.119 Nm
Rated Speed	3000 rpm
Torque Constant	0.054 Nm/A
Continuous Rated Output Power	37.4 W
Instantaneous Maximum Torque	0.357 Nm
No-Load Rotational Speed	4000 rpm
Pole Pairs	5
Instantaneous Maximum Current	6.6 A

Product Structure & Views

These views present product structure, mounting interfaces and relevant integration geometry for this SKU.



Mechanical View 1



Mechanical View 2

VIEW	FIELD	VALUE
Mechanical View 1	Shaft end diameter (upper section)	50.85 0/-0.015
	Shaft end diameter (lower section)	50.85 0/-0.1
	Shaft extension length	20±0.2
	Mounting face height	25±1
	Left boss width	5
	Main body outer diameter	65 +0.039/0
	Mounting boss thickness	2±0.3
	Total body length	50±1
Mechanical View 2	Shaft length	300±10
	Mounting hole diameter	4-4.5 THRU
	Mounting hole PCD	4-47±0.1
	Mounting face dimension	4-57

Technical Specifications

PARAMETER	VALUE	UNIT
Rated Torque	0.119	Nm
Rated Speed	3000	rpm
Torque Constant	0.054	Nm/A
Continuous Rated Output Power	37.4	W
Instantaneous Maximum Torque	0.357	Nm
No-Load Rotational Speed	4000	rpm
Pole Pairs	5	
Instantaneous Maximum Current	6.6	A
Rotational Back-EMF Constant	5.66	V/krpm
Continuous Rated Current	2.2	A
Dielectric strength	500VAC/1KHz/1mA/1s	
Insulation Resistance	100 MOhm 20C	
Position Feedback Device		
No-load Current	0.25	A
Rated Voltage	24	V
Rotor Inertia	0.19	kgcm ²

Technical Specifications - Continued

PARAMETER	VALUE	UNIT
Body Length	50	mm
Frame size	57	
Winding connection		
Housing shape	Square	
Noise	≤50	dB
Commutation angle	120°	°
Housing-to-Ambient Thermal Resistance	0.53	K/W
Motor efficiency	78	%
Line resistance	0.958	Ω
Maximum Winding Temperature	77.4	°C
Housing Type	No housing	
Line inductance	0.742	mH
Ambient temperature	29	°C
Duty Cycle	S1	
Motor Weight	0.42	g

Mounting, Shaft and Load Path

- Support the complete mounting face, preserve locating features and verify fastener engagement without distorting the housing.
- Align the shaft and coupling before tightening, and validate radial load, axial load, overhung distance, belt tension, inertia and shock for the installed mechanism.

Drive, Electrical and Motion Integration

- Coordinate supply, drive current limit, speed, torque and fault protection with the actual load and duty cycle.
- Use applicable wiring data for conductor identity, polarity, phase pairing, shielding and grounding; do not infer these from the product view.

Thermal, Cable and Commissioning Conditions

- Validate housing and winding temperature over the intended operating cycle, ambient condition, mounting heat path and enclosure airflow.
- Provide strain relief and service clearance, then commission at reduced energy and verify direction, current limits, motion response, temperature and fault behavior.

Integration Checklist

- | | |
|----|---|
| 01 | Confirm the exact-SKU drawing and parameter set. |
| 02 | Verify mounting geometry, locating features, shaft engagement, coupling alignment and service clearance. |
| 03 | Validate torque, speed, inertia, radial and axial loads, overhung distance and shock. |
| 04 | Set drive, current, motion, wiring, grounding and thermal boundaries from applicable product documentation. |
| 05 | Commission at reduced energy and verify direction, motion response, temperature and fault behavior. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-DC-SL06-M001 and is intended for dimensional evaluation and preliminary integration. It is not a applicable manufacturing drawing, motor or actuator application approval, wiring definition, drive-selection approval, machinery risk assessment, safety validation or production authorization. Before design freeze, installation or energization, verify all dimensions, mounting and locating features, moving envelopes, shaft or output geometry, permissible loads, alignment, supply and current limits, wiring, motion profile, duty cycle, thermal condition, cable routing, environmental boundaries, maintenance and fault response against the applicable EmbodyStack engineering data for this exact SKU. Validate the complete installed system under intended operating and fault conditions.