

ENGINEERING DOCUMENTATION

Frameless Torque Motor

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-FM-U01-OD085-T1NM-001	DRAFT-08 / 27 Aug 2026	Engineering Integration Reference

Integration Overview


Frameless torque motor for direct integration into a host rotary assembly. This guide supports rotor-stator alignment, air-gap control, bearing and load-path design, thermal extraction, electrical integration and staged commissioning.

Key Integration Facts


INTEGRATION ITEM	PUBLISHED VALUE
Rated Torque	1Nm
Rated Speed	3000 rpm
Body Outer Diameter	85 mm
Rotor Inner Diameter	42 mm
Axial Stack Length	8 mm

Product Structure & Views

These views present product structure, mounting interfaces and relevant integration geometry for this SKU.



Mechanical View 1



Mechanical View 2

VIEW	FIELD	VALUE
Mechanical View 1	U-phase wire terminal	U-phase
	W-phase wire terminal	W-phase
	V-phase wire terminal	V-phase
	Rotor magnetic pole marking	12 magnetic poles alternating N-S pattern
Mechanical View 2	Shaft diameter with tolerance	Ø +0.15/-0.25
	Shaft extension length (left side max)	6.5 mm max
	Shaft extension length (right side max)	4.5 mm max
	Power wire specification	Power wire (strip 5mm, tin coating)
	Cable minimum length	≥100 mm
	Motor outer diameter maximum	Ø0 mm max
	Motor inner bore minimum	Ø7 mm min
	Mounting hole diameter with tolerance	Ø2.5 +0.021/0
	Mounting outer diameter with tolerance	Ø5 0/-0.07
	Perpendicularity tolerance	Perpendicularity 0.02 relative to datum A
	Datum A (shaft centerline)	Datum A
	Mechanical Dimension	9

Overall Dimensions and Mounting Interface

PARAMETER	PUBLISHED VALUE	UNIT
Body Outer Diameter	85	mm
Rotor Inner Diameter	42	mm
Axial Stack Length	8	mm

- Confirm the stator, rotor, bore, axial stack, locating and retention geometry against the applicable exact-SKU drawing.
- The host housing and shaft must provide the required datum control without distorting the active motor components.

Rotor, Stator and Air-Gap Alignment

PARAMETER	PUBLISHED VALUE	UNIT
Rotor Inner Diameter	42	mm

- Control concentricity, axial position, runout and operating air gap through the complete tolerance and temperature range.
- Prevent contact, magnetic debris, impact and assembly forces from damaging the rotor or stator.

Bearing, Load Path and Retention

- The host bearing system must carry radial, axial and moment loads; do not infer bearing capability from motor torque or diameter.
- Provide positive rotor retention and verify overspeed, imbalance, shock and fault torque cases.

Electrical and Feedback Integration

PARAMETER	PUBLISHED VALUE	UNIT
Torque Constant	0.123	Nm/A
Number of Pole Pairs	8 pole pairs	

- Match the winding, drive current, voltage, commutation and feedback system to the exact SKU.
- Use current phase, sensor and insulation definitions; do not infer pin or phase identity from this guide.

Thermal Path and Duty Cycle

PARAMETER	PUBLISHED VALUE	UNIT
Rated Torque	1	Nm

- Design a verified heat path from the stator into the host structure and validate temperatures under the intended duty cycle.
- Peak torque and current are transient boundaries and require coordinated drive protection.

Assembly and Commissioning Validation

PARAMETER	PUBLISHED VALUE	UNIT
Rated Speed	3000	rpm
Rated Torque	1	Nm

- Check free rotation, air gap, retention, insulation and sensor alignment before energization.
- Commission at low energy, confirm commutation and direction, then validate the complete joint through intended load and fault cases.

Integration Checklist

- | | |
|----|--|
| 01 | Confirm the exact SKU, 2D package and applicable assembly data. |
| 02 | Verify stator, rotor, bore, stack, datums, retention and operating air gap. |
| 03 | Validate host bearings, shaft, housing stiffness, runout and thermal growth. |
| 04 | Confirm winding, drive, feedback, commutation and insulation compatibility. |
| 05 | Establish and validate the stator-to-housing thermal path. |
| 06 | Check free rotation and insulation before low-energy commissioning. |
| 07 | Validate full load, speed, temperature and credible fault cases. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-FM-U01-OD085-T1NM-001 and is intended for dimensional evaluation and preliminary integration. It is not a applicable manufacturing drawing, wiring definition, application approval, machinery risk assessment, safety validation or integration planning document. Before design freeze, machining, wiring or energization, verify all dimensions, tolerances, mounting and locating features, load boundaries, electrical interfaces, thermal conditions, cabling, grounding, protection, commissioning and applicable regulatory requirements against the applicable EmbodyStack engineering data for this exact SKU. Where this guide and applicable product documentation differ, the applicable product documentation governs. Validate the complete installed system under intended duty cycles, loads, accelerations, environmental conditions and credible fault cases.