

ENGINEERING DOCUMENTATION

High-Torque Cup Component Set

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-HG-S03-F32-R50	DRAFT-08 / 28 Aug 2026	Engineering Integration Reference

Integration Overview


High-Torque Cup Component Set for compact, coaxial, high-ratio rotary-axis integration. This guide supports interface planning, mounting alignment, duty validation, torsional behavior, lubrication, sealing and commissioning for ES-HG-S03-F32-R50.

Key Integration Facts


INTEGRATION ITEM	VALUE
Rated Torque	99 Nm
Instantaneous Maximum Torque	497 Nm
Start/Stop Peak Torque	281 Nm
Backlash	±0 arc sec
Reduction Ratio	50
Maximum Input Speed	4800 r/min
Frame Size	32
Weight	0.89 kg

Product Structure & Views


These views present the selected product structure, mounting interfaces and relevant integration geometry for this SKU.




Mechanical View 1



Mechanical View 2



Mechanical View 3



Mechanical View 4

VIEW	FIELD	VALUE
Mechanical View 1	Width symbol W	W, value Not specified
	4 counterbored mounting holes	4 holes $\varnothing 4.5$ with $\varnothing$ counterbore depth 4.5
	Pitch circle diameter	PCD $\varnothing 00$
	16 hole diameter	16 holes $\varnothing 5$
	4 hole diameter	4 holes $\varnothing 4.5$
	U label	U label, value Not specified
	Diameter	$\varnothing 2$
	Angular spacing	11.25°
	4 M5 threaded holes	4×M5 threaded holes
	Angular spacing	33.75°
	Angular spacing	45°
Mechanical View 2	Top overall width	42
	Step width with unilateral tolerance	28 +0.4/0
	Right-side minimum clearance	Minimum 1.5
	Left-side minimum length	Minimum 26.8
	Feature label T	T
	Local width	3.4
	Left outer diameter fit	Diameter 88 h7
	Left minimum diameter	Minimum diameter 86
	Left diameter	Diameter 52
	Left bore diameter fit	Diameter 26 H7
	Datum or feature letter D	D
	Right diameter	Diameter 50
	Right minimum diameter	Minimum diameter 86
	Outer Diameter	$\varnothing 110$ h6
	Axial Dimension	16 +0/-0.1
	Axial Installation Dimension	19.5 ± 0.2
	Datum or local label D	D
	Reference label	WAVE GENERATOR-A
Mechanical View 3	Number of holes and hole diameter	8 holes, diameter 9 mm
	Bolt circle diameter	Bolt circle diameter 40 mm
Mechanical View 4	View designation	View D
	Bolt circle or hole pattern diameter	Diameter 26
	Mounting/detail diameter	Diameter 32
	Threaded hole quantity and size	2 × M3 threaded holes
	Threaded hole depth or related dimension	6

Housing and Input Interface Dimensions

Housing Size: 32 Reduction Ratio: 50 Weight: 0.89 kg

WAVE GENERATOR	T (MM)	U	W
A14	16.3 +0.10	14 H7	5 JS9/P9
A19	21.8 +0.10	19 H7	6 JS9/P9
A22	24.8 +0.10	22 H7	
	25.3 +0.10		8 JS9/P9

Note: Dimensions in mm unless otherwise specified. Refer to the dimensional drawing for feature locations and datum definitions.

Input Interface Design Guidance

- Confirm the selected series, frame size, ratio and product form before using dimensions or interface geometry.
- Design the input shaft, key, engagement and axial retention for the verified torque and assembly state.
- Reserve assembly, sealing, inspection and removal access around input, housing and output interfaces.

Mounting, Alignment and Fastener Control

- Keep mounting faces flat, clean and free of burrs, debris and coating buildup.
- Control concentricity, tilt and axial position of input and housing datums.
- Tighten fasteners in a staged diagonal sequence and verify free, even rotation during assembly.

Torque, Speed and Duty Boundaries

PARAMETER	VALUE	UNIT
Rated Torque	99	Nm
Allowable Average Torque	140	
Start/Stop Peak Torque	281	
Instantaneous Maximum Torque	497	
Maximum Input Speed	4800	r/min
Average Input Speed	3500	
Design Life	10000	h

- Calculate torque and speed from acceleration, constant-speed, deceleration, dwell and reversal portions of the complete cycle.
- Treat start/stop peak and instantaneous maximum torque as transient boundaries.
- Validate life against actual torque, speed, shock frequency, lubrication, temperature, alignment and external loading.

Torque, Speed and Life Boundaries

PARAMETER	VALUE	INTEGRATION REQUIREMENT
Rated Torque	99 Nm	Use as the selected continuous output rating under validated duty and thermal conditions.
Allowable Average Torque	140 Nm	Calculate the actual time-weighted output torque over the complete cycle.
Start/Stop Peak Torque	281 Nm	Transient start/stop boundary; include acceleration and deceleration events.
Instantaneous Maximum Torque	497 Nm	Short-duration shock boundary only; do not use as a normal operating point.
Maximum Input Speed	4800 r/min	Maximum input-speed boundary; also verify motor and thermal limits.
Average Input Speed	3500 r/min	Validate the time-weighted average input speed over the complete duty cycle.
Design Life	10000 h	Design reference only; actual life depends on torque, speed, shock, lubrication and installation.

Transmission Accuracy and Torsional Rigidity

PARAMETER	VALUE	UNIT
Backlash	20	arc sec

- Installed positioning depends on reducer behavior, datum control, structural stiffness, motor and encoder errors and thermal growth.
- Use stiffness regions and transition torques when evaluating compliance, resonance, control gain and reversal.

Lubrication, Sealing and Thermal Control

- Use the specified lubricant, fill method and quantity for the exact configuration; do not mix incompatible lubricants.
- Provide compatible sealing at input, output and housing interfaces without distorting the reducer.
- Validate lubricant distribution and temperature for orientation, speed, load cycle and enclosure.
- Prevent chips, fibers, residue and moisture from entering gear or bearing cavities.

Output Bearing and External Load Path

- Calculate radial, axial and moment loads including offset, acceleration, gravity, process force, impact and emergency stops.
- Do not infer permissible external load from reducer torque capacity or frame size.
- Avoid forcing, impact, misalignment or host distortion through the output support during installation and operation.

Integration Checklist

- | | |
|----|---|
| 01 | Confirm the selected series, frame size, ratio and product form for this SKU. |
| 02 | Verify available dimensions and interface geometry without substituting a nearby configuration. |
| 03 | Check mounting-face flatness, concentricity, tilt, reliefs, cleanliness and support stiffness. |
| 04 | Verify input shaft, key, engagement length and axial retention. |
| 05 | Use staged diagonal tightening and verify free, even rotation. |
| 06 | Calculate average, start/stop peak and shock torque over the complete cycle. |
| 07 | Validate average and maximum input speed, design life and thermal condition. |
| 08 | Evaluate backlash, angular accuracy, hysteresis and stiffness for the control system. |
| 09 | Confirm lubricant, fill quantity, orientation, sealing and contamination controls. |
| 10 | Validate output radial, axial and moment loads using applicable bearing data. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-HG-S03-F32-R50 and supports preliminary dimensional evaluation and integration. It is not a manufacturing drawing, reducer selection approval, bearing-load approval, lubrication specification, machinery risk assessment, safety validation or integration planning document. Before design freeze, assembly or commissioning, verify all dimensions, datum geometry, fits, interfaces, retention, fasteners, torque and speed duty, shock cases, torsional behavior, external loads, lubrication, sealing, temperature, contamination and maintenance requirements against the current EmbodyStack engineering data for this exact SKU. Validate the complete reducer, motor, host structure, output load, motion cycle, guarding, fault cases and applicable regulatory requirements under intended operating conditions.