

ENGINEERING DOCUMENTATION

High-Torque Cup Unit Type II

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-HG-S06-F32-R160	DRAFT-08 / 28 Aug 2026	Engineering Integration Reference

Integration Overview


High-Torque Cup Unit Type II for compact, coaxial, high-ratio rotary-axis integration. This guide supports interface planning, mounting alignment, duty validation, torsional behavior, lubrication, sealing and commissioning for ES-HG-S06-F32-R160.

Key Integration Facts

INTEGRATION ITEM	VALUE
Rated Torque	178 Nm
Instantaneous Maximum Torque	892 Nm
Start/Stop Peak Torque	484 Nm
Backlash	±0 arc sec
Reduction Ratio	160
Maximum Input Speed	4800 r/min
Frame Size	32
Weight	3.11 kg

3D Orientation Reference

This axonometric reference provides a quick orientation check for the reducer body, input interface and mounting relationship of ES-HG-S06-F32-R160.



Axonometric Orientation View

Orientation reference only. Use the exact-SKU parameter table and mechanical drawing for dimensions, hole geometry, fits and machining decisions.

Exact-SKU Interface Cross-Reference

INTEGRATION TOPIC	EXACT-SKU REFERENCE
Reducer envelope and configuration	Frame Size: 32; Reduction Ratio: 160; Weight: 3.11 kg. Confirm hole geometry, datum features and fits in the exact-SKU mechanical drawing.
Torque and speed boundaries	Rated Torque: 178 Nm; Start/Stop Peak Torque: 484 Nm; Instantaneous Maximum Torque: 892 Nm; Maximum Input Speed: 4800 r/min. Confirm hole geometry, datum features and fits in the exact-SKU mechanical drawing.
Input and mounting interfaces	Confirm this interface from the exact-SKU mechanical drawing.

These views present the selected product structure, mounting interfaces and relevant integration geometry for this SKU.



VIEW	FIELD	VALUE
Mechanical View 1	Mounting flange outer diameter	Φ13 h7
	Mounting flange intermediate diameter	Φ12
	Mounting hole diameter	Φ8
	Inner bore diameter	Φ6 H7
	Inner bore small diameter	Φ0
	Mounting holes position and count (top)	0-69×2
	Overall height (top section)	36.2
	Step height	23.6 0/-0.1
	Edge width	2.2
	Central axial length	14.2
	Step depth (top right)	5.5
	Middle height	17
	Step depth (bottom right)	5.5
	Lower section height	12
	Horizontal distance 1	57
	Horizontal distance 2	60
	Overall width (reference)	62±0.2 (reference)
	Shaft diameter (bottom)	16.3 +0.1/0
	Shaft bore diameter (bottom)	Φ6
	Lower flange mounting diameter	Φ0 h7
	Maximum outer diameter	Φ88
	Mounting holes position and count (bottom)	0-105×2
	Mechanical Dimensio	5.5
Mechanical View 2	Threaded hole count and specification	12× M6 threaded holes
	Keyway width with tolerance class	5 JS9 (bilateral symmetric tolerance, keyway width)
	Through-hole count and diameter	12× Φ.5 through holes
	Flange outer diameter	Φ25
	Central bore diameter with fit tolerance	Φ4 H7 (clearance fit bore)
Mechanical View 3	Mounting threaded hole specification and count	8× M10 threaded holes, evenly distributed on bolt circle
	Bolt circle diameter (PCD)	Φ5 mm bolt circle diameter

Overall Dimensions and Input Interface

PARAMETER	VALUE	UNIT
Frame Size	32	
Reduction Ratio	160	
Weight	3.11	kg

Input Interface Design Guidance

- Confirm the selected series, frame size, ratio and product form before using dimensions or interface geometry.
- Design the input shaft, key, engagement and axial retention for the verified torque and assembly state.
- Reserve assembly, sealing, inspection and removal access around input, housing and output interfaces.

Mounting, Alignment and Fastener Control

- Keep mounting faces flat, clean and free of burrs, debris and coating buildup.
- Control concentricity, tilt and axial position of input and housing datums.
- Tighten fasteners in a staged diagonal sequence and verify free, even rotation during assembly.

Torque, Speed and Duty Boundaries

PARAMETER	VALUE	UNIT
Rated Torque	178	Nm
Allowable Average Torque	281	
Start/Stop Peak Torque	484	
Instantaneous Maximum Torque	892	
Starting Torque	15	
Maximum Input Speed	4800	r/min
Average Input Speed	3500	
Design Life	15000	h

- Calculate torque and speed from acceleration, constant-speed, deceleration, dwell and reversal portions of the complete cycle.
- Treat start/stop peak and instantaneous maximum torque as transient boundaries.
- Validate life against actual torque, speed, shock frequency, lubrication, temperature, alignment and external loading.

Torque, Speed and Life Boundaries

PARAMETER	VALUE	INTEGRATION REQUIREMENT
Rated Torque	178 Nm	Use as the selected continuous output rating under validated duty and thermal conditions.
Allowable Average Torque	281 Nm	Calculate the actual time-weighted output torque over the complete cycle.
Start/Stop Peak Torque	484 Nm	Transient start/stop boundary; include acceleration and deceleration events.
Instantaneous Maximum Torque	892 Nm	Short-duration shock boundary only; do not use as a normal operating point.
Maximum Input Speed	4800 r/min	Maximum input-speed boundary; also verify motor and thermal limits.
Average Input Speed	3500 r/min	Validate the time-weighted average input speed over the complete duty cycle.
Design Life	15000 h	Design reference only; actual life depends on torque, speed, shock, lubrication and installation.

Transmission Accuracy and Torsional Rigidity

PARAMETER	VALUE	UNIT
Backlash	±0	arc sec
Angle Transmission Accuracy	1	arc min
Hysteresis Loss		
Torsional Rigidity K1	6.7	Nm/rad
Torsional Rigidity K2	11	
Torsional Rigidity K3	12	
Torsional Rigidity T1	29	Nm
Torsional Rigidity T2	108	

- Installed positioning depends on reducer behavior, datum control, structural stiffness, motor and encoder errors and thermal growth.
- Use stiffness regions and transition torques when evaluating compliance, resonance, control gain and reversal.

Lubrication, Sealing and Thermal Control

- Use the specified lubricant, fill method and quantity for the exact configuration; do not mix incompatible lubricants.
- Provide compatible sealing at input, output and housing interfaces without distorting the reducer.
- Validate lubricant distribution and temperature for orientation, speed, load cycle and enclosure.
- Prevent chips, fibers, residue and moisture from entering gear or bearing cavities.

Output Bearing and External Load Path

- Calculate radial, axial and moment loads including offset, acceleration, gravity, process force, impact and emergency stops.
- Do not infer permissible external load from reducer torque capacity or frame size.
- Avoid forcing, impact, misalignment or host distortion through the output support during installation and operation.

Integration Checklist

- | | |
|----|---|
| 01 | Confirm the selected series, frame size, ratio and product form for this SKU. |
| 02 | Verify available dimensions and interface geometry without substituting a nearby configuration. |
| 03 | Check mounting-face flatness, concentricity, tilt, reliefs, cleanliness and support stiffness. |
| 04 | Verify input shaft, key, engagement length and axial retention. |
| 05 | Use staged diagonal tightening and verify free, even rotation. |
| 06 | Calculate average, start/stop peak and shock torque over the complete cycle. |
| 07 | Validate average and maximum input speed, design life and thermal condition. |
| 08 | Evaluate backlash, angular accuracy, hysteresis and stiffness for the control system. |
| 09 | Confirm lubricant, fill quantity, orientation, sealing and contamination controls. |
| 10 | Validate output radial, axial and moment loads using applicable bearing data. |

[View SKU Product Datasheet](#)[Request controlled 2D drawing](#)[Request controlled STEP review](#)[Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-HG-S06-F32-R160 and supports preliminary dimensional evaluation and integration. It is not a manufacturing drawing, reducer selection approval, bearing-load approval, lubrication specification, machinery risk assessment, safety validation or integration planning document. Before design freeze, assembly or commissioning, verify all dimensions, datum geometry, fits, interfaces, retention, fasteners, torque and speed duty, shock cases, torsional behavior, external loads, lubrication, sealing, temperature, contamination and maintenance requirements against the current EmbodyStack engineering data for this exact SKU. Validate the complete reducer, motor, host structure, output load, motion cycle, guarding, fault cases and applicable regulatory requirements under intended operating conditions.