

ENGINEERING DOCUMENTATION

Standard Hat Unit Type I

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-HG-S24-F17-R100	DRAFT-08 / 28 Aug 2026	Engineering Integration Reference

Integration Overview


Standard Hat Unit Type I for compact, coaxial, high-ratio rotary-axis integration. This guide supports interface planning, mounting alignment, duty validation, torsional behavior, lubrication, sealing and commissioning for ES-HG-S24-F17-R100.

Key Integration Facts


INTEGRATION ITEM	VALUE
Rated Torque	24 Nm
Instantaneous Maximum Torque	108 Nm
Start/Stop Peak Torque	54 Nm
Backlash	±0 arc sec
Reduction Ratio	100
Maximum Input Speed	7300 r/min
Frame Size	17
Weight	0.54 kg

Product Structure & Views


These views present the selected product structure, mounting interfaces and relevant integration geometry for this SKU.




Mechanical View 1



Mechanical View 2



Mechanical View 3



Mechanical View 4

VIEW	FIELD	VALUE
Mechanical View 1	Top overall width	26.5 mm
	Top inner width	19 mm
	Small step width	3 mm
	Left maximum clearance	MAX 2.1 mm
	Right minimum clearance	MIN 1 mm
	Local axial distance	3.9 mm
	Minimum fit diameter	MIN diameter 45 mm
	Maximum fit diameter	MAX diameter 38 mm
	Diameter 80 tolerance	Diameter 80 mm, upper deviation -0.01 mm, lower deviation -0.03 mm
	Diameter 60 H7 fit	Diameter 60 H7
	Diameter 28	Diameter 28 mm
	Diameter 60 h6 fit	Diameter 60 h6
	Diameter 80 h7 fit	Diameter 80 h7
	Datum D	Datum D
	Bottom local width with tolerance	12.5 mm, upper deviation 0 mm, lower deviation -0.1 mm
	Bottom left length	13.4 ±0.2 mm
	View title	Wave Generator - A
	Datum T	Datum T
Mechanical View 2	16 holes diameter	16 × $\varnothing$ 5, depth/countersink callout 6.5
	16 M3 threaded holes	16 × M3 threaded holes, depth/countersink callout 6
	Width label W	W dimension label, value not specified in this crop
	Diameter 54	$\varnothing$ 4
	Label U	U label, value not specified in this crop
	Angle 18 degrees	18°
	2 M4 threaded holes	2 × M4 threaded holes
	Diameter 22 hole	$\varnothing$ 2
Mechanical View 3	12 hole diameter callout	12 holes, diameter 3.5
	Process holes quantity	Process holes x4; diameter Not specified
	M3 set screw threaded holes quantity and thread size	4 threaded holes, M3, for set screw
	Hole pattern angular spacing	15 degrees angular spacing
	Hole pattern pitch circle diameter	Pitch circle diameter 74
Mechanical View 4	View designation	View D
	Diameter 16 feature	Diameter 16 mm
	Two M2.5 through threaded holes	2 × M2.5 through
	Triangle/V symbol 5 callout	5
	Diameter 12 feature	Diameter 12 mm

Housing and Input Interface Dimensions

Housing Size: 17 Reduction Ratio: 100 Weight: 0.54 kg

WAVE GENERATOR	T (MM)	U	W
A8	9.4 +0.10	8 H7	3 JS9/P9
A11	12.8 +0.10	11 H7	4 JS9/P9

Note: Dimensions in mm unless otherwise specified. Refer to the dimensional drawing for feature locations and datum definitions.

Input Interface Design Guidance

- Confirm the selected series, frame size, ratio and product form before using dimensions or interface geometry.
- Design the input shaft, key, engagement and axial retention for the verified torque and assembly state.
- Reserve assembly, sealing, inspection and removal access around input, housing and output interfaces.

Mounting, Alignment and Fastener Control

- Keep mounting faces flat, clean and free of burrs, debris and coating buildup.
- Control concentricity, tilt and axial position of input and housing datums.
- Tighten fasteners in a staged diagonal sequence and verify free, even rotation during assembly.

Torque, Speed and Duty Boundaries

PARAMETER	VALUE	UNIT
Rated Torque	24	Nm
Allowable Average Torque	39	
Start/Stop Peak Torque	54	
Instantaneous Maximum Torque	108	
Maximum Input Speed	7300	r/min
Average Input Speed	3500	
Design Life	15000	h

- Calculate torque and speed from acceleration, constant-speed, deceleration, dwell and reversal portions of the complete cycle.
- Treat start/stop peak and instantaneous maximum torque as transient boundaries.
- Validate life against actual torque, speed, shock frequency, lubrication, temperature, alignment and external loading.

Torque, Speed and Life Boundaries

PARAMETER	VALUE	INTEGRATION REQUIREMENT
Rated Torque	24 Nm	Use as the selected continuous output rating under validated duty and thermal conditions.
Allowable Average Torque	39 Nm	Calculate the actual time-weighted output torque over the complete cycle.
Start/Stop Peak Torque	54 Nm	Transient start/stop boundary; include acceleration and deceleration events.
Instantaneous Maximum Torque	108 Nm	Short-duration shock boundary only; do not use as a normal operating point.
Maximum Input Speed	7300 r/min	Maximum input-speed boundary; also verify motor and thermal limits.
Average Input Speed	3500 r/min	Validate the time-weighted average input speed over the complete duty cycle.
Design Life	15000 h	Design reference only; actual life depends on torque, speed, shock, lubrication and installation.

Transmission Accuracy and Torsional Rigidity

PARAMETER	VALUE	UNIT
Backlash	20	arc sec

- Installed positioning depends on reducer behavior, datum control, structural stiffness, motor and encoder errors and thermal growth.
- Use stiffness regions and transition torques when evaluating compliance, resonance, control gain and reversal.

Lubrication, Sealing and Thermal Control

- Use the specified lubricant, fill method and quantity for the exact configuration; do not mix incompatible lubricants.
- Provide compatible sealing at input, output and housing interfaces without distorting the reducer.
- Validate lubricant distribution and temperature for orientation, speed, load cycle and enclosure.
- Prevent chips, fibers, residue and moisture from entering gear or bearing cavities.

Output Bearing and External Load Path

- Calculate radial, axial and moment loads including offset, acceleration, gravity, process force, impact and emergency stops.
- Do not infer permissible external load from reducer torque capacity or frame size.
- Avoid forcing, impact, misalignment or host distortion through the output support during installation and operation.

Integration Checklist

- | | |
|----|---|
| 01 | Confirm the selected series, frame size, ratio and product form for this SKU. |
| 02 | Verify available dimensions and interface geometry without substituting a nearby configuration. |
| 03 | Check mounting-face flatness, concentricity, tilt, reliefs, cleanliness and support stiffness. |
| 04 | Verify input shaft, key, engagement length and axial retention. |
| 05 | Use staged diagonal tightening and verify free, even rotation. |
| 06 | Calculate average, start/stop peak and shock torque over the complete cycle. |
| 07 | Validate average and maximum input speed, design life and thermal condition. |
| 08 | Evaluate backlash, angular accuracy, hysteresis and stiffness for the control system. |
| 09 | Confirm lubricant, fill quantity, orientation, sealing and contamination controls. |
| 10 | Validate output radial, axial and moment loads using applicable bearing data. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-HG-S24-F17-R100 and supports preliminary dimensional evaluation and integration. It is not a manufacturing drawing, reducer selection approval, bearing-load approval, lubrication specification, machinery risk assessment, safety validation or integration planning document. Before design freeze, assembly or commissioning, verify all dimensions, datum geometry, fits, interfaces, retention, fasteners, torque and speed duty, shock cases, torsional behavior, external loads, lubrication, sealing, temperature, contamination and maintenance requirements against the current EmbodyStack engineering data for this exact SKU. Validate the complete reducer, motor, host structure, output load, motion cycle, guarding, fault cases and applicable regulatory requirements under intended operating conditions.