ENGINEERING DOCUMENTATION

Ultra-Short Hollow Shaft Gear Unit

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-HG-S28-F32-R100	DRAFT-08 / 26 Aug 2026	Engineering Integration Reference

Integration Overview

Hollow-shaft harmonic gear gear unit with integrated product interfaces for the selected configuration for compact, coaxial, high-ratio rotary axes. This guide supports host-interface design, wave-generator input integration, mounting alignment, load-cycle validation, torsional behavior, lubrication, sealing and commissioning for ES-HG-S28-F32-R100.

Key Integration Facts

INTEGRATION ITEM	PUBLISHED VALUE
Rated Torque	96 N·m
Instantaneous Maximum Torque	420 N·m
Start/Stop Peak Torque	233 N·m
Reduction Ratio	100
Maximum Input Speed	4800 r/min
Frame Size	32
Weight	3.56 kg

Product Structure & Views

These views present the selected product structure, mounting interfaces and relevant integration geometry for this SKU.



Mechanical View 1



Mechanical View 2



Mechanical View 3

VIEW	FIELD	VALUE
Mechanical View 1	12 holes diameter 5.5	12 × Ø5.5 holes
	Bolt circle diameter	Ø132 bolt circle diameter
	Angular offset	15 degrees angular offset
	Diameter 40.5 circular feature	Ø40.5
	6 M3 threaded holes depth 6	6 × M3 threaded holes, depth 6
Mechanical View 2	Maximum outside diameter fit	Diameter 147 h7
	Upper shaft diameter fit	Diameter 45 h7
	Upper bore diameter fit	Diameter 36 H7
	Local height dimension	10
	Right-side local height dimension	12
	Left middle height dimension	29
	Left overall height dimension	53
	Left lower height dimension	17
	Central lower height dimension	15
	Bottom local height dimension	5
	Lower bore diameter fit	Diameter 36 H7
	Lower shaft diameter fit	Diameter 85 h7
	Outside diameter	Diameter 115
	Bottom outside diameter fit	Diameter 142 h7 not explicitly marked with diameter symbol in OCR crop
Mechanical View 3	Mounting hole pitch circle diameter	Pitch circle diameter 99
	12-hole diameter and depth callout	12 holes, diameter 5.5, depth 18.5
	12 M5 threaded holes depth	12 M5 threaded holes, depth 5.5
	Central interface diameter	Diameter 40.5
	6 M3 threaded holes depth	6 M3 threaded holes, depth 6

Overall Dimensions and Input Interface

PARAMETER	PUBLISHED VALUE	UNIT
Frame Size	32	
Weight	3.56	kg

- Confirm the selected series, frame size and ratio before using dimensions or interface geometry. Do not substitute a nearby frame or product form.
- Design the input shaft, key, effective engagement and axial retention to transmit the verified torque without uncontrolled wave-generator axial movement.
- Reserve assembly, sealing, inspection and removal access around the input, housing and output interfaces.

Mounting, Alignment and Fastener Control

- Keep mounting faces flat, clean and free of burrs, raised holes, debris and coating buildup. Confirm reliefs and chamfers prevent interference.
- Seat the fixed and flexible gear members in the host structure before inserting the wave generator. Do not force engagement in a misaligned condition.
- Control concentricity, tilt and axial position of the input and housing datums. Insert the wave generator smoothly without excessive force on its bearing.
- Tighten fasteners in a staged diagonal sequence using the applicable torque and locking specification. Verify free, even rotation during assembly.

Torque, Speed and Duty Boundaries

PARAMETER	PUBLISHED VALUE	UNIT
Rated Torque	96	N·m
Allowable Average Torque	151	N·m
Start/Stop Peak Torque	233	N·m
Instantaneous Maximum Torque	420	N·m
Maximum Input Speed	4800	r/min
Average Input Speed	3500	r/min
Design Life	10000	h

- Calculate average torque and average input speed from the complete acceleration, constant-speed, deceleration, dwell and reversal cycle.
- Treat start/stop peak and instantaneous maximum torque as transient boundaries. Do not use either value as a continuous operating point.
- Validate design life against actual torque, speed, shock frequency, lubrication, temperature, alignment and external loading.

Published Torque, Speed and Life Boundaries

PARAMETER	PUBLISHED VALUE	INTEGRATION REQUIREMENT
Rated Torque	96 N·m	Use as the selected continuous output rating under validated duty and thermal conditions.
Allowable Average Torque	151 N·m	Calculate the actual time-weighted output torque over the complete cycle.
Start/Stop Peak Torque	233 N·m	Transient start/stop boundary; include acceleration and deceleration events.
Instantaneous Maximum Torque	420 N·m	Short-duration shock boundary only; do not use as a normal operating point.
Maximum Input Speed	4800 r/min	Maximum input-speed boundary; also verify motor and thermal limits.
Average Input Speed	3500 r/min	Validate the time-weighted average input speed over the complete duty cycle.
Design Life	10000 h	Design reference only; actual life depends on torque, speed, shock, lubrication and installation.

Transmission Accuracy and Torsional Rigidity

PARAMETER	PUBLISHED VALUE	UNIT
Angle Transmission Accuracy	1	arc min
Hysteresis Loss	1	arc min
Torsional Rigidity K1	2.7	×10⁴N·m/rad
Torsional Rigidity K2	3.7	×10⁴N·m/rad
Torsional Rigidity K3	4.7	×10⁴N·m/rad
Torsional Rigidity T1	14	N·m
Torsional Rigidity T2	48	N·m

- Installed positioning performance depends on reducer behavior, datum control, fastener distortion, motor and encoder errors, host stiffness and thermal growth.
- Use the published stiffness regions and transition torques when evaluating compliance, resonance, control gain and direction reversal.

Published Accuracy and Torsional Rigidity Boundaries

PARAMETER	PUBLISHED VALUE	INTEGRATION REQUIREMENT
Angle Transmission Accuracy	1 arc min	Installed system accuracy also depends on datum, encoder, motor and structural errors.
Hysteresis Loss	1 arc min	Include in direction-reversal and closed-loop positioning evaluation.
Torsional Rigidity K1	2.7 ×10⁴N·m/rad	Applies to the published low-torque stiffness region.
Torsional Rigidity K2	3.7 ×10⁴N·m/rad	Applies to the published intermediate stiffness region.
Torsional Rigidity K3	4.7 ×10⁴N·m/rad	Applies to the published upper stiffness region.
Torsional Rigidity T1	14 N·m	Published transition torque for stiffness-region interpretation.
Torsional Rigidity T2	48 N·m	Published transition torque for stiffness-region interpretation.

Lubrication, Sealing and Thermal Control

- Use only the current lubricant, fill method and quantity for the exact configuration. Do not mix incompatible lubricants.
- Provide compatible static and dynamic sealing at the input, output and housing interfaces without distorting the reducer or restricting motion.
- Validate lubricant distribution and temperature for the installed orientation, speed, load cycle and enclosure.
- Prevent chips, fibers, cleaning residue, moisture and other contamination from entering the gear or bearing cavities during assembly and service.

Output Bearing and External Load Path

- Calculate radial, axial and moment loads at the output, including offset, acceleration, gravity, process force, impact and emergency-stop cases.
- Do not infer permissible external load from reducer torque capacity or frame size. Use applicable output-bearing data and safety criteria.
- Avoid forcing, impact, misalignment or host distortion through the output support bearing during installation and operation.

Integration Checklist

01	Confirm the drawing, published parameters and applicable assembly data identify this SKU.
02	Verify series, frame size, ratio, product form and input-interface dimensions.
03	Check mounting-face flatness, concentricity, tilt, chamfers, reliefs, cleanliness and support stiffness.
04	Verify input shaft, key, engagement length and axial wave-generator retention.
05	Assemble the fixed and flexible gear members before inserting the wave generator.
06	Use staged diagonal tightening and verify free, even rotation throughout assembly.
07	Calculate average, start/stop peak and shock torque over the complete operating cycle.
08	Validate average and maximum input speed, design life and installed thermal condition.
09	Evaluate backlash, angular accuracy, hysteresis and stiffness regions for the control system.
10	Confirm exact lubricant, fill quantity, orientation, sealing and contamination controls.
11	Validate output radial, axial and moment loads using applicable bearing data.
12	Include specified 2D, STEP, assembly, lubrication and bearing-load data in integration planning.

View SKU Product Datasheet **Request controlled 2D drawing** **Request controlled STEP review** **Request a Quote**

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-HG-S28-F32-R100 and is intended for dimensional evaluation and preliminary integration. It is not a applicable manufacturing drawing, reducer selection approval, bearing-load approval, lubrication specification, machinery risk assessment, safety validation or integration planning document and must not be used as the sole basis for machining, shaft or key manufacture, fastener selection, sealing, lubricant filling or final integration. Before design freeze, assembly or commissioning, verify all dimensions, datum geometry, fits, shaft and key interfaces, wave-generator retention, fastener engagement and tightening controls, torque and speed duty, shock cases, torsional accuracy and rigidity, external output loads, lubrication, sealing, temperature, contamination and maintenance requirements against the applicable EmbodyStack engineering data for this exact SKU. Where this guide and applicable product documentation differ, the applicable product documentation governs. Validate the complete reducer, motor, host structure, output load, motion cycle, guarding, fault cases and applicable regulatory requirements under intended operating conditions.