

ENGINEERING DOCUMENTATION

Rotary Servo Motor

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-SM-A01-040S-TOP32NM-100W-003	DRAFT-08 / 27 Aug 2026	Engineering Integration Reference

Integration Overview

Closed-loop rotary servo motor for specified motion axes. This guide supports mechanical mounting, shaft and coupling integration, feedback and brake planning, cable routing, thermal validation and staged commissioning.

Key Integration Facts


INTEGRATION ITEM	PUBLISHED VALUE
Rated Torque	0.32 Nm
Rated Speed	3000 rpm
Flange Size	40 mm

Product Structure & Views


These views present product structure, mounting interfaces and relevant integration geometry for this SKU.




Mechanical View 3




Mechanical View 4



Mechanical View 5



Mechanical View 6



Mechanical View 8

VIEW	FIELD	VALUE
Mechanical View 3	Connector terminal/cavity number	Cavity/pin position 2
	Connector pin number 1	Pin 1
	Connector pin number 4	Pin 4
	Connector pin number 3	Pin 3
Mechanical View 4	Upper row terminal numbers	Connector upper row terminals: 6, 4, 2
	Lower row terminal numbers	Connector lower row terminals: 5, 3, 1
Mechanical View 5	Section view identifier	Section A-A
	Detail view scale	Scale 2:1
	Keyway slot width	3 mm, +0/-0.014
	Section feature dimension	9.2 mm
	Shaft end locating length	12 mm
	Datum A	Datum A
	M3 thread depth	M3 thread depth 8 mm
	Hole depth	Hole depth 8 mm
	Shaft end small diameter	Diameter 8 mm, +0/-0.013
	Shaft end major diameter	Diameter 30 mm, +0/-0.021
	Shaft extension length	20.5 mm ±0.2
	Shaft shoulder offset	2.8 mm
	Shoulder thickness	5 mm
	Shaft end total length	23.8 mm ±0.8
	Main body length	108.2 mm ±1
Mechanical View 6	Connector body marking	SM-6P
	Power wire label	Power wire
	Power wire length	Length ≥500
	Feedback wire label	Feedback wire
	Feedback wire length	Length ≥500
	Upper maximum height	Maximum height 15
	Mounting hole quantity and diameter	2 holes, diameter 3.5
	Mounting hole angular position	45 degrees
	Mounting face vertical size	40
	Mounting face horizontal size	40
	Mounting circle diameter tolerance	Diameter 45 ± 0.2
Mechanical View 8	Torque axis unit	Torque T in N.m
	Speed axis unit	Rotational speed n in rpm
	Torque scale tick values	Torque axis ticks: 0 to 1.12 N.m
	Speed scale tick values	Speed axis ticks: 1000 to 6000 rpm

VIEW	FIELD	VALUE
Intermittent operation torque curve	Intermittent torque curve shown on torque-speed graph	
Continuous operation torque curve	Continuous torque curve shown on torque-speed graph; visible point label 0.352	

Overall Dimensions and Mounting Interface

PARAMETER	PUBLISHED VALUE	UNIT
Flange Size	40	mm

- Confirm the mounting face, locating feature, shaft geometry, fastener engagement and removal clearance against the applicable exact-SKU drawing.
- Mount the motor on a flat, rigid interface and avoid using fasteners to pull a misaligned assembly into position.

Shaft, Coupling and Load Path

PARAMETER	PUBLISHED VALUE	UNIT
Rotor Inertia	0.033	kgcm ²

- Align the driven shaft and coupling before tightening; validate radial, axial and moment loads against applicable bearing-load data.
- Do not hammer, uncontrolled press-fit or transmit installation force through the motor bearings.

Electrical, Feedback and Brake Integration

PARAMETER	PUBLISHED VALUE	UNIT
Position Feedback Device	23-bit multi-turn communication optical absolute encoder	

- Use only the current winding, feedback, brake and connector definitions for this exact SKU.
- Verify drive compatibility, polarity, current limits, feedback direction and brake sequencing before enabling torque.

Thermal, Duty and Environmental Conditions

PARAMETER	PUBLISHED VALUE	UNIT
Rated Torque	0.32	Nm
Operating Temperature	20 40	°C

- Validate winding and housing temperature under the installed duty cycle, ambient condition, mounting heat path and enclosure airflow.
- Published peak values are transient boundaries and must not be treated as continuous operating ratings.

Cable Routing, Grounding and EMC

PARAMETER	PUBLISHED VALUE	UNIT
Position Feedback Device	23-bit multi-turn communication optical absolute encoder	

- Provide strain relief and bend radius through the full machine motion envelope.
- Separate motor power, brake and feedback wiring and terminate shields according to the specified system grounding architecture.

Commissioning and Motion Validation

PARAMETER	PUBLISHED VALUE	UNIT
Rated Speed	3000	rpm
Rated Torque	0.32	Nm

- Commission at low energy with the transmission unloaded or safely restrained, then confirm direction, feedback polarity, brake final integration, current limit and fault response.
- Validate the complete axis through intended acceleration, speed, load, stop and fault cycles during integration planning.

Integration Checklist

- | | |
|----|--|
| 01 | Confirm the exact SKU, 2D drawing and applicable wiring data. |
| 02 | Verify mounting, shaft, coupling, alignment, fasteners and removal clearance. |
| 03 | Validate radial and axial loads, inertia, acceleration and credible shock cases. |
| 04 | Confirm drive, winding, feedback, brake and connector compatibility. |
| 05 | Set current, speed, acceleration and thermal limits from the installed duty cycle. |
| 06 | Verify cable routing, shielding, grounding, strain relief and bend radius. |
| 07 | Commission at low energy before validating the full machine cycle. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-SM-A01-040S-TOP32NM-100W-003 and is intended for dimensional evaluation and preliminary integration. It is not a applicable manufacturing drawing, wiring definition, application approval, machinery risk assessment, safety validation or integration planning document. Before design freeze, machining, wiring or energization, verify all dimensions, tolerances, mounting and locating features, load boundaries, electrical interfaces, thermal conditions, cabling, grounding, protection, commissioning and applicable regulatory requirements against the applicable EmbodyStack engineering data for this exact SKU. Where this guide and applicable product documentation differ, the applicable product documentation governs. Validate the complete installed system under intended duty cycles, loads, accelerations, environmental conditions and credible fault cases.