

ENGINEERING DOCUMENTATION

Rotary Servo Motor

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-SM-A02-060S-T1P27NM-400W-001	DRAFT-08 / 27 Aug 2026	Engineering Integration Reference

Integration Overview



Closed-loop rotary servo motor for specified motion axes. This guide supports mechanical mounting, shaft and coupling integration, feedback and brake planning, cable routing, thermal validation and staged commissioning.

Key Integration Facts


INTEGRATION ITEM	PUBLISHED VALUE
Rated Torque	1.27 N·m
Rated Speed	3000 rpm
Flange Size	60 mm

Product Structure & Views

These views present product structure, mounting interfaces and relevant integration geometry for this SKU.




Mechanical View 2




Mechanical View 6

Mechanical View 4



Mechanical View 7



VIEW	FIELD	VALUE
Mechanical View 2	Feedback wire connector pin 5 position	Pin 5
	Feedback wire connector pin 15 position	Pin 15
	Feedback wire connector pin 10 position	Pin 10
	Feedback wire connector pin 1 position	Pin 1
	Feedback wire connector pin 6 position	Pin 6
	Feedback wire connector pin 11 position	Pin 11
Mechanical View 4	Connector pin number	Pin 2
	Connector pin number	Pin 1
	Connector pin number	Pin 3
	Connector pin number	Pin 4
Mechanical View 6	Power wire label	Power Wire
	Feedback wire label	Feedback Wire
	Mounting hole diameter	4- ϕ 5
	Mounting hole angular position	45°
	Mounting flange square dimension	160
	Mounting hole pitch circle diameter	$\varnothing 0 \pm 0.1$
Mechanical View 7	Keyway width	16 mm
	Keyway depth	5 mm
	Cable minimum length	L≥200 mm
	Keyway width	5 mm
	Motor outer diameter	72 mm
	Shaft diameter	$\varnothing 0 / -0.016$ mm
	Keyway width	16 0/-0.13 mm
	Shaft inner diameter	$\varnothing 4 0 / -0.011$ mm
	Mounting hole depth	3 mm
	Mounting hole spacing	6 mm
	Mounting flange length	30±1 mm
	Motor overall length	150±1.5 mm
Mechanical View 8	Chart Title	Performance Curve
	Torque Y-axis	T(N.m)
	Speed X-axis	n(rpm)
	Intermittent Operation Mode	Intermittent
	Continuous Operation Mode	Continuous
	Torque Scale Values	Y-axis: 0 to 4.5 N.m
	Speed Scale Values	X-axis: 0 to 6000 rpm
	Intermittent Mode Starting Torque	4.2 N.m at 0 rpm

VIEW	FIELD	VALUE
Intermittent Mode Torque Point	3.81 N.m at approximately 3000 rpm	
Continuous Mode Starting Torque	1.4 N.m at 0 rpm	
Continuous Mode Torque Point	1.27 N.m at approximately 3000 rpm	

Overall Dimensions and Mounting Interface

PARAMETER	PUBLISHED VALUE	UNIT
Flange Size	60	mm

- Confirm the mounting face, locating feature, shaft geometry, fastener engagement and removal clearance against the applicable exact-SKU drawing.
- Mount the motor on a flat, rigid interface and avoid using fasteners to pull a misaligned assembly into position.

Shaft, Coupling and Load Path

PARAMETER	PUBLISHED VALUE	UNIT
Rotor Inertia	0.51	kgcm ²

- Align the driven shaft and coupling before tightening; validate radial, axial and moment loads against applicable bearing-load data.
- Do not hammer, uncontrolled press-fit or transmit installation force through the motor bearings.

Electrical, Feedback and Brake Integration

PARAMETER	PUBLISHED VALUE	UNIT
Position Feedback Device	2500 PPR incremental encoder	

- Use only the current winding, feedback, brake and connector definitions for this exact SKU.
- Verify drive compatibility, polarity, current limits, feedback direction and brake sequencing before enabling torque.

Thermal, Duty and Environmental Conditions

PARAMETER	PUBLISHED VALUE	UNIT
Rated Torque	1.27	Nm
Operating Temperature	20 40	°C

- Validate winding and housing temperature under the installed duty cycle, ambient condition, mounting heat path and enclosure airflow.
- Published peak values are transient boundaries and must not be treated as continuous operating ratings.

Cable Routing, Grounding and EMC

PARAMETER	PUBLISHED VALUE	UNIT
Position Feedback Device	2500 PPR incremental encoder	

- Provide strain relief and bend radius through the full machine motion envelope.
- Separate motor power, brake and feedback wiring and terminate shields according to the specified system grounding architecture.

Commissioning and Motion Validation

PARAMETER	PUBLISHED VALUE	UNIT
Rated Speed	3000	rpm
Rated Torque	1.27	Nm

- Commission at low energy with the transmission unloaded or safely restrained, then confirm direction, feedback polarity, brake final integration, current limit and fault response.
- Validate the complete axis through intended acceleration, speed, load, stop and fault cycles during integration planning.

Integration Checklist

- | | |
|----|--|
| 01 | Confirm the exact SKU, 2D drawing and applicable wiring data. |
| 02 | Verify mounting, shaft, coupling, alignment, fasteners and removal clearance. |
| 03 | Validate radial and axial loads, inertia, acceleration and credible shock cases. |
| 04 | Confirm drive, winding, feedback, brake and connector compatibility. |
| 05 | Set current, speed, acceleration and thermal limits from the installed duty cycle. |
| 06 | Verify cable routing, shielding, grounding, strain relief and bend radius. |
| 07 | Commission at low energy before validating the full machine cycle. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-SM-A02-060S-T1P27NM-400W-001 and is intended for dimensional evaluation and preliminary integration. It is not a applicable manufacturing drawing, wiring definition, application approval, machinery risk assessment, safety validation or integration planning document. Before design freeze, machining, wiring or energization, verify all dimensions, tolerances, mounting and locating features, load boundaries, electrical interfaces, thermal conditions, cabling, grounding, protection, commissioning and applicable regulatory requirements against the applicable EmbodyStack engineering data for this exact SKU. Where this guide and applicable product documentation differ, the applicable product documentation governs. Validate the complete installed system under intended duty cycles, loads, accelerations, environmental conditions and credible fault cases.