

ENGINEERING DOCUMENTATION

Rotary Servo Motor

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-SM-A03-130G-T5P39NM-850W-001	DRAFT-08 / 27 Aug 2026	Engineering Integration Reference

Integration Overview


Closed-loop rotary servo motor for specified motion axes. This guide supports mechanical mounting, shaft and coupling integration, feedback and brake planning, cable routing, thermal validation and staged commissioning.

Key Integration Facts


INTEGRATION ITEM	PUBLISHED VALUE
Rated Torque	5.39 Nm
Rated Speed	1500 rpm
Rated Voltage	220 VAC
Flange Size	130 mm

Product Structure & Views


These views present product structure, mounting interfaces and relevant integration geometry for this SKU.




Mechanical View 1




Mechanical View 2



Mechanical View 4



Mechanical View 6



VIEW	FIELD	VALUE
Mechanical View 1	Keyway label	Keyway
	Key length	36
	Keyway width	8
	Aviation connector dot orientation note	Aviation connector dot near front shaft
	Item balloon 2	Item 2
	Geometric tolerance	Geometric tolerance 0.08 relative to datum A
	Shaft keyway label	Keyway
	Threaded hole specification	CM6L20
	Datum A	Datum A
	Front output shaft diameter	Diameter 22, +0/-0.013
	Geometric tolerance value	Geometric tolerance 0.08
	Shaft extension length	25, +0/-0.2
	Housing outer diameter	Diameter 110, +0/-0.035
	Geometric tolerance value	Geometric tolerance 0.04
	End step dimensions	5 and 13.5
	Front shaft end to flange distance	55 ±1
	Main body length	139 ±1.5
	Key Width	7
	Feature Identifier 1	1
Mechanical View 2	Motor connector label	Motor connector
	Encoder connector label	Encoder connector
	Mounting hole pitch circle diameter	Pitch circle diameter Ø145 ±0.2
	Mounting hole quantity and diameter	4 holes, Ø9
	Left mounting hole angular position	45 degrees
	Right mounting hole angular position	45 degrees
	Square mounting flange side length	Square flange 130
Mechanical View 4	Connector Contact Letter Designation	A, B, C, D, ...
Mechanical View 6	Connector Contact Letter Designation	A, B, C, D, ...
Mechanical View 9	Short-term workspace maximum torque point	Speed 2400 rpm, Torque 16.2 Nm
	Transition point between short-term and continuous workspace	Speed 1500 rpm, Torque 5.39 Nm
	Continuous workspace maximum speed point (upper curve)	Speed 3500 rpm, Torque 4.4 Nm
	Continuous workspace maximum speed point (lower curve)	Speed 3500 rpm, Torque 2.31 Nm
	Speed axis label	Rotational speed n in rpm
	Torque axis label	Torque T in N.m

VIEW	FIELD	VALUE
Torque Scale	0-15 Nm	
Motor Speed Scale	0-3500 rpm	

Overall Dimensions and Mounting Interface

PARAMETER	PUBLISHED VALUE	UNIT
Flange Size	130	mm

- Confirm the mounting face, locating feature, shaft geometry, fastener engagement and removal clearance against the applicable exact-SKU drawing.
- Mount the motor on a flat, rigid interface and avoid using fasteners to pull a misaligned assembly into position.

Shaft, Coupling and Load Path

PARAMETER	PUBLISHED VALUE	UNIT
Rotor Inertia	12.86 ()	Kg-cm ²

- Align the driven shaft and coupling before tightening; validate radial, axial and moment loads against applicable bearing-load data.
- Do not hammer, uncontrolled press-fit or transmit installation force through the motor bearings.

Electrical, Feedback and Brake Integration

PARAMETER	PUBLISHED VALUE	UNIT
Rated Voltage	220	VAC
Position Feedback Device	17-bit multi-turn communication magnetic absolute encoder	

- Use only the current winding, feedback, brake and connector definitions for this exact SKU.
- Verify drive compatibility, polarity, current limits, feedback direction and brake sequencing before enabling torque.

Thermal, Duty and Environmental Conditions

PARAMETER	PUBLISHED VALUE	UNIT
Rated Torque	5.39	Nm
Operating Temperature	-20 40	°C

- Validate winding and housing temperature under the installed duty cycle, ambient condition, mounting heat path and enclosure airflow.
- Published peak values are transient boundaries and must not be treated as continuous operating ratings.

Cable Routing, Grounding and EMC

PARAMETER	PUBLISHED VALUE	UNIT
Position Feedback Device	17-bit multi-turn communication magnetic absolute encoder	

- Provide strain relief and bend radius through the full machine motion envelope.
- Separate motor power, brake and feedback wiring and terminate shields according to the specified system grounding architecture.

Commissioning and Motion Validation

PARAMETER	PUBLISHED VALUE	UNIT
Rated Speed	1500	rpm
Rated Torque	5.39	Nm

- Commission at low energy with the transmission unloaded or safely restrained, then confirm direction, feedback polarity, brake final integration, current limit and fault response.
- Validate the complete axis through intended acceleration, speed, load, stop and fault cycles during integration planning.

Integration Checklist

- | | |
|----|--|
| 01 | Confirm the exact SKU, 2D drawing and applicable wiring data. |
| 02 | Verify mounting, shaft, coupling, alignment, fasteners and removal clearance. |
| 03 | Validate radial and axial loads, inertia, acceleration and credible shock cases. |
| 04 | Confirm drive, winding, feedback, brake and connector compatibility. |
| 05 | Set current, speed, acceleration and thermal limits from the installed duty cycle. |
| 06 | Verify cable routing, shielding, grounding, strain relief and bend radius. |
| 07 | Commission at low energy before validating the full machine cycle. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-SM-A03-130G-T5P39NM-850W-001 and is intended for dimensional evaluation and preliminary integration. It is not a applicable manufacturing drawing, wiring definition, application approval, machinery risk assessment, safety validation or integration planning document. Before design freeze, machining, wiring or energization, verify all dimensions, tolerances, mounting and locating features, load boundaries, electrical interfaces, thermal conditions, cabling, grounding, protection, commissioning and applicable regulatory requirements against the applicable EmbodyStack engineering data for this exact SKU. Where this guide and applicable product documentation differ, the applicable product documentation governs. Validate the complete installed system under intended duty cycles, loads, accelerations, environmental conditions and credible fault cases.