

ENGINEERING DOCUMENTATION

Rotary Servo Motor

Dimensional & Integration Guide

DOCUMENT	REVISION / ISSUE	STATUS
DIG-ES-SM-L01-060S-V48-T1P27NM-400W-001	DRAFT-08 / 27 Aug 2026	Engineering Integration Reference

Integration Overview


Closed-loop rotary servo motor for specified motion axes. This guide supports mechanical mounting, shaft and coupling integration, feedback and brake planning, cable routing, thermal validation and staged commissioning.

Key Integration Facts


INTEGRATION ITEM	PUBLISHED VALUE
Rated Torque	1.27 N·m
Rated Speed	3000 rpm
Rated Voltage	48 VDC
Flange Size	60 mm

Product Structure & Views


These views present product structure, mounting interfaces and relevant integration geometry for this SKU.




Mechanical View 2




Mechanical View 4



Mechanical View 5



Mechanical View 6



Mechanical View 8

VIEW	FIELD	VALUE
Mechanical View 2	Feedback wire connector pin 6	Pin number 6
	Feedback wire connector pin 4	Pin number 4
	Feedback wire connector pin 2	Pin number 2
	Feedback wire connector pin 5	Pin number 5
	Feedback wire connector pin 3	Pin number 3
	Feedback wire connector pin 1	Pin number 1
Mechanical View 4	Connector terminal number 1	Pin/terminal position label: 1
	Connector terminal number 2	Pin/terminal position label: 2
	Connector terminal number 3	Pin/terminal position label: 3
	Connector terminal number 4	Pin/terminal position label: 4
Mechanical View 5	Key width	5 mm
	Key length	16 mm
	Connector identifier	SC-06
	Key	Key feature
	Connector body marking	SM-6P
	Cable length	L ≥500 mm
	Perpendicularity tolerance	Perpendicularity tolerance 0.04 relative to datum A
	Concentricity or coaxiality tolerance	Diameter tolerance zone 0.04 relative to datum A
	Shaft key feature label	Key feature
	Shaft keyway width	5 mm
	Cable or connector label	CM5L15
	Body height	72.5 mm
	Main shaft diameter	Diameter 50 mm, +0/-0.016 mm
	Shaft step diameter	Diameter 16 mm, +0/-0.13 mm
	Shaft end diameter	Diameter 14 mm, +0/-0.011 mm
	Datum A	Datum A
	End step distance	3 mm
	Runout tolerance	Runout tolerance 0.02 mm
	Flange or shoulder thickness	6 mm
	Axial length (near section)	30±1 mm
	Axial length (far section)	97±1.5 mm
	Keyway height (alternate view)	5 mm
Mechanical View 6	power wire label	Power Wire
	feedback wire label	Feedback Wire
	mounting hole count and diameter	4 × $\varnothing$ 5.5
	outer diameter	$\varnothing$ 70 ±0.1

VIEW	FIELD	VALUE
Angle callout	45°	
Square flange envelope size	Square 60 mm envelope	
Mechanical View 8	Performance curve title	Performance Curve
	Torque vertical axis	Torque T, unit N.m as shown
	Speed horizontal axis	Speed n, unit rpm as shown
	Intermittent operating region	Intermittent operating region
	Continuous operating region	Continuous operating region
	Torque axis tick values	Torque scale ticks: 0 to 4 in 0.5 increments
	Speed axis tick values	Speed scale ticks: 0, 1000, 2000, 3000, 4000 rpm
	Peak torque callout	Peak torque callout: 3.81 N.m
	Continuous torque curve callout	Continuous torque curve callout: 1.27 N.m
	Continuous curve left-side torque callout	Continuous curve left-side torque callout: 1.4 N.m
	Maximum speed callout	Maximum speed callout: 3900 rpm

Overall Dimensions and Mounting Interface

PARAMETER	PUBLISHED VALUE	UNIT
Flange Size	60	mm

- Confirm the mounting face, locating feature, shaft geometry, fastener engagement and removal clearance against the applicable exact-SKU drawing.
- Mount the motor on a flat, rigid interface and avoid using fasteners to pull a misaligned assembly into position.

Shaft, Coupling and Load Path

PARAMETER	PUBLISHED VALUE	UNIT
Rotor Inertia	0.38 / 0.384	Kg·cm ²

- Align the driven shaft and coupling before tightening; validate radial, axial and moment loads against applicable bearing-load data.
- Do not hammer, uncontrolled press-fit or transmit installation force through the motor bearings.

Electrical, Feedback and Brake Integration

PARAMETER	PUBLISHED VALUE	UNIT
Rated Voltage	48	VDC

- Use only the current winding, feedback, brake and connector definitions for this exact SKU.
- Verify drive compatibility, polarity, current limits, feedback direction and brake sequencing before enabling torque.

Thermal, Duty and Environmental Conditions

PARAMETER	PUBLISHED VALUE	UNIT
Rated Torque	1.27	N·m
Operating Temperature	-20 to 40	°C

- Validate winding and housing temperature under the installed duty cycle, ambient condition, mounting heat path and enclosure airflow.
- Published peak values are transient boundaries and must not be treated as continuous operating ratings.

Cable Routing, Grounding and EMC

- Provide strain relief and bend radius through the full machine motion envelope.
- Separate motor power, brake and feedback wiring and terminate shields according to the specified system grounding architecture.

Commissioning and Motion Validation

PARAMETER	PUBLISHED VALUE	UNIT
Rated Speed	3000	rpm
Rated Torque	1.27	N·m

- Commission at low energy with the transmission unloaded or safely restrained, then confirm direction, feedback polarity, brake final integration, current limit and fault response.
- Validate the complete axis through intended acceleration, speed, load, stop and fault cycles during integration planning.

Integration Checklist

- | | |
|----|--|
| 01 | Confirm the exact SKU, 2D drawing and applicable wiring data. |
| 02 | Verify mounting, shaft, coupling, alignment, fasteners and removal clearance. |
| 03 | Validate radial and axial loads, inertia, acceleration and credible shock cases. |
| 04 | Confirm drive, winding, feedback, brake and connector compatibility. |
| 05 | Set current, speed, acceleration and thermal limits from the installed duty cycle. |
| 06 | Verify cable routing, shielding, grounding, strain relief and bend radius. |
| 07 | Commission at low energy before validating the full machine cycle. |

[View SKU Product Datasheet](#) [Request controlled 2D drawing](#) [Request controlled STEP review](#) [Request a Quote](#)

Engineering Use and Verification Notice

01. This Dimensional & Integration Guide applies only to EmbodyStack SKU ES-SM-L01-060S-V48-T1P27NM-400W-001 and is intended for dimensional evaluation and preliminary integration. It is not a applicable manufacturing drawing, wiring definition, application approval, machinery risk assessment, safety validation or integration planning document. Before design freeze, machining, wiring or energization, verify all dimensions, tolerances, mounting and locating features, load boundaries, electrical interfaces, thermal conditions, cabling, grounding, protection, commissioning and applicable regulatory requirements against the applicable EmbodyStack engineering data for this exact SKU. Where this guide and applicable product documentation differ, the applicable product documentation governs. Validate the complete installed system under intended duty cycles, loads, accelerations, environmental conditions and credible fault cases.